

MECHANICAL SYMBOLS	
GENERAL	PIPING
	FLOOR DRAIN
	FLOOR SINK
	ROOF DRAIN
	VARIABLE FREQUENCY DRIVE
	ELECTRONICALLY COMMUTATED MOTOR
	POINT OF CONNECTION OF NEW TO EXISTING WORK
	POINT OF DEMOLITION TO EXISTING WORK
	DEMOLITION KEYED NOTE
	NEW WORK KEYED NOTE
	ABBREVIATION
	NUMBER
	RISER TAG
	MATCH LINE
SEE SHEET NO. X#.#	MATCH LINE
	VIEW #
X#.#	SHEET #
	SECTION VIEW REFERENCE
X#.#	SHEET #
DUCTWORK	
	NEW DUCTWORK
	EXISTING DUCTWORK TO REMAIN
	EXISTING DUCTWORK TO BE DEMOLISHED
	DIRECTION OF AIRFLOW
	DUCTWORK CONTINUATION
	RECTANGULAR EXHAUST/RETURN DUCTWORK DOWN
	RECTANGULAR EXHAUST/RETURN DUCTWORK UP
	RECTANGULAR SUPPLY DUCTWORK DOWN
	RECTANGULAR SUPPLY DUCTWORK UP
	ROUND DUCTWORK DOWN
	ROUND DUCTWORK UP
	GRILLE/REGISTER/DIFFUSER TAG
	AUTOMATIC CONTROL (OR MOTOR OPERATED) DAMPER
	FIRE DAMPER
	FSD - FIRE/SMOKE DAMPER
	SD - SMOKE DAMPER
	MANUAL VOLUME (OR BALANCING) DAMPER
	FLEXIBLE DUCTWORK CONNECTION
	ACCESS DOOR
	SMACNA DUCT PRESSURE CLASSIFICATION
	DUCT PRESSURE DESIGNATIONS: 1. NUMBER INDICATES SMACNA PRESSURE CLASS. 2. THE SYMBOL CONTINUES THE ASSIGNMENT UNTIL THE DUCT TERMINATES OR ANOTHER SYMBOL APPEARS.
NOTE: NOT ALL SYMBOLS LISTED ABOVE MAY BE USED OR APPEAR IN THESE DRAWINGS.	
PIPING	
	NEW PIPING
	EXISTING PIPING TO REMAIN
	EXISTING PIPING TO BE DEMOLISHED
	NEW PIPE CONNECTION
	DIRECTION OF FLOW
	DIRECTION OF PIPE PITCH, DOWN
	PIPE CONTINUATION
	ECCENTRIC PIPE REDUCER
	ORIFICE PIPE UNION
	PIPE CAP
	PIPE ELBOW, 30° HORIZONTAL
	PIPE ELBOW, 45° HORIZONTAL
	PIPE ELBOW, 90° HORIZONTAL
	PIPE ELBOW, TURNED DOWN
	PIPE ELBOW, TURNED UP
	PIPE REDUCER/INCREASER
	PIPE TEE, 45° HORIZONTAL
	PIPE TEE, 90° HORIZONTAL
	PIPE TEE, DOWN
	PIPE TEE, UP
	PIPE UNION
CONTROLS	
	AUTOMATIC AIR VENT WITH ISOLATION
	BACKFLOW PREVENTER
	FLEXIBLE PIPE CONNECTOR (OR CONNECTION)
	AQUASTAT
	METER
	PIPE ALIGNMENT GUIDE
	PIPE ANCHOR
	PIPE EXPANSION JOINT
	PIPE SLEEVE
	PIPE WELL
	PRESSURE GAUGE
	PUMP
	STEAM TRAP
	TEST PLUG
	THERMOMETER
DUCTWORK	
	THREADED HOSE CONNECTION
	ANGLE VALVE
	BALL VALVE
	BUTTERFLY VALVE
	CHECK VALVE
	GAS COCK
	GATE VALVE
	GLOBE VALVE
	MANUAL BALANCING VALVE
	MANUAL THREE-WAY, TWO-POSITION VALVE
	NEEDLE VALVE
	OS&Y GATE VALVE
	PRESSURE REDUCING/REGULATING VALVE
	PRESSURE/SAFETY RELIEF VALVE
	SOLENOID VALVE
	STRAINER
	THERMOSTATIC MIXING VALVE
	THREE-WAY, MODULATING AUTOMATIC CONTROL VALVE
	THREE-WAY, TWO-POSITION AUTOMATIC CONTROL VALVE
	TWO-WAY, MODULATING AUTOMATIC CONTROL VALVE
	TWO-WAY, TWO-POSITION AUTOMATIC CONTROL VALVE
	Y-STRAINER CHECK VALVE
NOTE: NOT ALL SYMBOLS LISTED ABOVE MAY BE USED OR APPEAR IN THESE DRAWINGS.	

MECHANICAL ABBREVIATIONS	
ACD	AUTOMATIC CONTROL DAMPER
ACV	AUTOMATIC CONTROL VALVE
AD	ACCESS DOOR
AFF	ABOVE FINISHED FLOOR
AHU	AIR HANDLING UNIT
AP	ACCESS PANEL
APD	AIR PRESSURE DROP
AS	AIR SEPARATOR
ASU	AIR SUPPLY UNIT
B	BOTTLE
BAS	BUILDING AUTOMATION SYSTEM
BASC	BUILDING AUTOMATION SYSTEM CONTRACTOR
BFV	BUTTERFLY VALVE
BFW	BOILER FEED WATER
BHP	BRAKE HORSEPOWER
BOD	BOTTOM OF DUCT
BOI	BOTTOM OF INSULATION
BOP	BOTTOM OF PIPE
BT	BUCKET TRAILER
BTU	BRITISH THERMAL UNIT
BTUH	BRITISH THERMAL UNIT PER HOUR
BV	BALL VALVE
BWR	BOILER WATER RETURN
BWS	BOILER WATER SUPPLY
C	COMMON
CBV	CIRCUIT BALANCING VALVE
CC	CLOUDING COIL
CFH	CFH FEET PER HOUR
CFM	CUBIC FT PER MINUTE
CHWR	CHILLED WATER RETURN
CHWS	CHILLED WATER SUPPLY
CK	GAS COCK
CKV	CHECK VALVE
CO	CLEANOUT
COND	CONDENSATE
COP	COEFFICIENT OF PERFORMANCE
CO2	CARBON DIOXIDE
CR	COLD RETURN
CT	COOLING TOWER
CU	CONDENSING UNIT
CV	CONTROL VALVE
CWR	CONDENSER WATER RETURN
CWS	CONDENSER WATER SUPPLY
D	DRAIN
DB	DRY BULB
DCW	COLD (OR CITY) WATER
DG	DOOR GRILLE
DHW	DOMESTIC HOT WATER
DHWVR	DOMESTIC HOT WATER RECIRCULATION
DN	DOWN
DOAS	DEDICATED OUTDOOR AIR SYSTEM
DS	DUCT SLEEVE
DTR	DUAL TEMPERATURE WATER RETURN
DTS	DUAL TEMPERATURE WATER SUPPLY
-E	EXHAUST
EA	EXHAUST AIR
EAD	EXHAUST AIR DAMPER
EAT	EXHAUST AIR AND TEMPERATURE
EBB	ELECTRIC BASEBOARD
EC	ELECTRICAL CONTRACTOR
ECM	ELECTRONICALLY COMMUTATED MOTOR
EDH	ELECTRIC DUCT HEATER
EER	ENERGY EFFICIENCY RATIO
EF	EXHAUST FAN
EG	ETHYLENE GLYCOL
EJ	EXPANSION JOINT
ERCP	ELECTRIC RADIANT CEILING PANEL
ESP	EVAPORATIVE COOLING PANEL
ESUH	ELECTRIC CABINET UNIT HEATER
ET	EXPANSION TANK
EUH	ELECTRIC UNIT HEATER
EWT	ENTERING WATER TEMPERATURE
F	FAHRENHEIT
FC	FLEXIBLE CONNECTOR (OR CONNECTION)
FD	FLOOR DRAIN
FCU	FAN COIL UNIT
FID	FIRE DAMPER
FSD	FIRE SUPPLY DAMPER
FFA	FROM FLOOR ABOVE
FFB	FROM FLOOR BELOW
FLA	FULL LOAD AMPS
FOB	FLAT ON BOTTOM
FOT	FLAT ON TOP
FPP	FINS PER FOOT
FPI	FINS PER INCH
FPM	FEET PER MINUTE
FS	FLOOR SYSTEM
FTR	FACE TO RADIATION
FV	FACE VELOCITY
G	GAS
GA	GAUGE
GPM	GALLONS PER MINUTE
GTR	GEOTHERMAL RETURN
GTS	GEOTHERMAL SUPPLY
GV	GATE VALVE
HC	HEATING COIL
HG	HOT GAS
HP	HORSEPOWER
HPS	HIGH PRESSURE STEAM
HWR	HOT WATER RETURN
HWS	HOT WATER SUPPLY
HX	HEAT EXCHANGER
HZ	HIGH ZONE
IPLV	INTEGRATED PART LOAD VALUE
KG	KEYED GUARD
KH	KITCHEN HOOD
LAT	LEAVING AIR TEMPERATURE
LPS	LOW PRESSURE STEAM
LWT	LEAVING WATER TEMPERATURE
LZ	LOW ZONE
MAU	MAKE-UP AIR UNIT
MBH	THOUSAND BRITISH THERMAL UNITS PER HOUR
MC	MECHANICAL CONTRACTOR
MCA	MINIMUM CIRCUIT AMPLIty
MOPC	MAXIMUM OVERCURRENT PROTECTION
MOD	MOTOR OPERATED DAMPER
MU	MAKE-UP WATER
NC	NORMALLY CLOSED
NC	NORMALLY CONTRACT
NO	NORMALLY OPEN
NPLV	NONSTANDARD PART LOAD VALUE
NPSH	NET POSITIVE SUCTION HEAD
NTS	NOT TO SCALE
OA	OUTDOOR AIR
OAD	OUTDOOR AIR DAMPER
OSD	OPEN SITE DRAIN
OS&Y	OUTSIDE STEM AND YOKE
P	PUMP
PD	PRESSURE DROP
PG	PROPYLENE GLYCOL
PHC	PREHEAT COIL
PRD	PRESSURE RELIEF DOOR
PRV	PRESSURE REDUCING (OR REGULATING) VALVE
PS	PIPE SLEEVE
PSI	POUNDS PER SQUARE INCH
-R	RETURN
RA	RETURN AIR
RAD	RETURN AIR DAMPER
RCP	RADIAN CEILING PANEL
REF	REFRIGERANT
RF	RETURN FAN
RG	REFRIGERANT GAS
RHC	REHEAT COIL
RL	REFRIGERANT LIQUID
RPM	REVOLUTIONS PER MINUTE
RS	REFRIGERANT SUCTION
RV	RELIEF VALVE
S	SUPPLY
SA	SUPPLY AIR
SAN	SANITARY
SD	SMOKE DAMPER
SEER	SEASONAL ENERGY EFFICIENCY RATIO
SP	STATIC PRESSURE
SS	STAINLESS STEEL
SST	SATURATED SUCTION TEMPERATURE
ST	STORM
STM	STRAINER
STR	STRAINER
SUH	SUSPENDED UNIT HEATER
T	THERMOSTAT
-T	TRANSFER
TDH	TOTAL DYNAMIC HEAD
TDV	TRIPLE DUTY VALVE
TFA	TO FLOOR ABOVE
TFB	TO FLOOR BELOW
TSB	TOTAL STATIC PRESSURE
UC	UNDERCUT DOOR
UH	UNIT HEATER
V	VENT
VAV	VARIABLE AIR VOLUME
VD	VOLUME DAMPER
VFD	VARIABLE FREQUENCY DRIVE
VTR	VENT THROUGH ROOF
WB	WET BULB
WC	WATER COLUMN
WG	WATER GAUGE
WL	WATER LOUVER
WMS	WIRE MESH SCREEN
WPD	WATER PRESSURE DROP
VSD	VARIABLE SPEED DRIVE

NOTE: NOT ALL ABBREVIATIONS LISTED ABOVE MAY BE USED OR APPEAR IN THESE DRAWINGS.



ILLINOIS SPORTS
FACILITIES AUTHORITY



ISSUE/REVISION:
REV DATE DESCRIPTION
1/30/2026 ISSUED FOR BID

PROJECT: RATE FIELD - HVAC FY2026

333 WEST 35TH STREET
CHICAGO, IL 60616

DRAWING TITLE: MECHANICAL TITLE SHEET

DESIGNED BY: MO


CHECKED BY: CC

PROJECT NO: 25080

SCALE: NO SCALE

NOTE SHEET NO.

M0.01





ISSUE/REVISION:
REV DATE DESCRIPTION
1/30/2026 ISSUED FOR BID



PROJECT:
RATE FIELD - HVAC FY2026

333 WEST 35TH STREET
CHICAGO, IL 60616

DRAWING TITLE:
MECHANICAL PLAN - 400 LEVEL

DESIGNED BY: MO
CHECKED BY: CC
PROJECT NO: 25080
SCALE: 1/32" = 1'-0"
SHEET NO.

M1.02





ISSUE/REVISION:		
REV	DATE	DESCRIPTION
	1/30/2026	ISSUED FOR BID


PROJECT:
RATE FIELD - HVAC FY2026



333 WEST 35TH STREET
CHICAGO, IL 60616

DRAWING TITLE:
MECHANICAL PLAN - 500 LEVEL


DESIGNED BY: MO
CHECKED BY: CC
PROJECT NO: 25080
SCALE: 1/32" = 1'-0"
SHEET NO.

M1.03








1 MECHANICAL PLAN - ELEV. 3 & 4 MACHINE ROOM - 400 LEVEL



3 MECHANICAL PLAN - ELEV. 5 & 6 MACHINE ROOM - 600 LEVEL


M2.01






1 TYPICAL DUCT CONSTRUCTION DETAILS

SCALE: NO SCALE




2 SINGLE BLADE VOLUME DAMPER

SCALE: NO SCALE




3 FLEXIBLE CONNECTION

SCALE: NO SCALE




4 HORIZONTAL TWO PIPE AIR HANDLING UNIT

SCALE: NO SCALE




5 HORIZONTAL TWO PIPE FAN COIL UNIT

SCALE: NO SCALE



6 HIGH POINT MANUAL VENT DETAIL

SCALE: NO SCALE



7 LOW POINT MANUAL DRAIN DETAIL

SCALE: NO SCALE



AIR HANDLING UNIT SCHEDULE (AHU)																																					
EQUIP. TAG		GENERAL										SUPPLY FAN						COOLING DATA						HEATING DATA						ELECTRICAL DATA			NOTES				
ABB.	NO.	LOCATION	MFR	MODEL	OPERATING WEIGHT (LBS)	COIL HAND	LENGTH (IN)	WIDTH (IN)	HEIGHT (IN)	MIN. OA	TOTAL AIR FLOW (CFM)	ESP (IN. WC)	TYPE	QTY.	FAN RPM	RPM	HP (EACH)	BHP (EACH)	TYPE	EAT DB/WB (DEG.F)	LAT DB/WB (DEG.F)	EWT (DEG.F)	LWT (DEG.F)	WATER FLOW (GPM)	WATER PD (FT. HD.)	TOTAL CAPACITY (MBH)	SENSIBLE CAPACITY (MBH)	TYPE	EAT (DEG.F)	LAT (DEG.F)	TOTAL CAPACITY (KW)	STAGES	SENSIBLE CAPACITY (MBH)	VOLTS	HZ	PHASE	
AHU	5B-3	ELEVATOR 3, 4 MACHINE ROOM	CARRIER	42DHA208RGMGDKAMKA	309	RIGHT	36	28	19-3/4	300	2000	0.75	DIRECT	1	1108	1108	1	-	ETHYLENE GLYCOL	82.3 / 68.9	54.5 / 53.6	44	54	20.9	33.2	96.1	61.40	ELECTRIC COIL	50	61.1	7	2	23.90	460	60	3	SEE BELOW
AHU	6-3B	ELEVATOR 7,8,9,10 MACHINE ROOM	CARRIER	42BHE30LGSR13408GG	350	RIGHT	40-1/4	48	32-1/4	400	3400	0.75	BELT	1	1114	1114	2	1.84	ETHYLENE GLYCOL	81.3 / 68.1	55.4 / 54.7	44	54	31.1	22.3	142.4	97.1	ELECTRIC COIL	50	73.2	25	3	85.3	480	60	3	SEE BELOW
AHU	7D-1	ELEVATOR 5, 6 MACHINE ROOM	CARRIER	42DHA168RGMGDAMKA	309	LEFT	37-3/4	47	21-1/2	200	1600	0.75	DIRECT	1	1341	1341	1	-	ETHYLENE GLYCOL	81.9 / 68.6	56.4 / 55.2	44	54	16.7	28.8	76.6	50.7	ELECTRIC COIL	50	67.4	9.9	2	33.8	460	60	3	SEE BELOW
NOTES:																																					
1. MANUFACTURER PROVIDED 1 YEAR PARTS WARRANTY ON ENTIRE UNIT. MECHANICAL CONTRACTOR TO PROVIDE A 1 YEAR LABOR WARRANTY FOR THE ENTIRE UNIT. 2. FACTORY HEATER FUSING AND 40A DISCONNECT (AHU-5B-3 AND AHU-7D-1) 3. MOTOR AND ELECTRIC HEAT CONTROLS WITH FUSED DISCONNECT 41 TO 60 AMPS (AHU-6-3B) 4. VIBRATION ISOLATION AND OVERHEAD SUSPENSION BRACKETS. 5. CONDENSATE OVERFLOW SWITCH. 6. MULTI-SLOPED STAINLESS STEEL DRAIN PANS UNDER ANY COOLING COIL. 7. MANUFACTURER CERTIFIED START-UP. 8. 350 PSIG COIL TEST PRESSURE, 300 PSIG OPERATION PRESSURE. 9. STANDARD 1" THROWAWAY FILTER. PROVIDE (1) EXTRA SET OF FILTERS FOR OWNERS STOCK. 10. CHILLED WATER COILS ARE SCHEDULED WITH 30% EG. 11. DOUBLE WALL 2" 1" FIBERGLASS AND SOLID INNER LINER. 12. REAR RETURN / FRONT SUPPLY. 13. SINGLE POINT POWER CONNECTION. 14. PROVIDE WITH FILTER RACK.																																					

ELARA
elaraeng.com | (708) 236-0300

ISFA
ILLINOIS SPORTS
FACILITIES AUTHORITY



HYDRONIC FAN COIL UNITS (FCU)																													
EQUIP. TAG		GENERAL										PERFORMANCE						ELECTRICAL						NOTES					
ABB.	NO.	LOCATION	SERVICE	MFR	MODEL	TYPE	OPERATING WEIGHT (LBS)	LENGTH (IN)	WIDTH (IN)	HEIGHT (IN)	AIRFLOW (CFM)	ESP (IN. WC)	TOTAL COOLING CAPACITY (MBH)	SENSIBLE COOLING CAPACITY (MBH)	EAT DB/WB (°F)	LAT DB/WB (°F)	CHW FLOW (GPM)	FILTERS	VOLTS	HZ	PHASE								
FCU	1	ISFA OFFICE SUITE	ISFA OFFICE SUITE	CARRIER	42DCA12	HORIZONTAL DUCTED	169	46	29.5	16.5	1200	0.3	44.6	25.5	75 / 67	54.6 / 54.3	9.9	MERV 13	115	60	1	SEE BELOW							
FCU	2	ISFA OFFICE SUITE	ISFA OFFICE SUITE	CARRIER	42DCA12	HORIZONTAL DUCTED	169	46	29.5	16.5	1200	0.3	44.6	25.5	75 / 67	54.6 / 54.3	9.9	MERV 13	115	60	1	SEE BELOW							
NOTES:																													
1. CAPACITIES ARE BASED ON HIGH FAN SPEED. 2. COIL CONNECTION HAND TO BE DETERMINED BY MECHANICAL CONTRACTOR. 3. EXISTING ELECTRIC HEATING COIL SHALL REMAIN AND BE RE-USED. 4. COORDINATE CONTROLS WITH BUILDING TEMPERATURE CONTROLS CONTRACTOR FOR THERMOSTATS, CONTROL VAVES, INTERCONNECTION OF FAN COIL AND ELECTRIC HEATING COIL. 5. INCLUDE 1" THROWAWAY FILTERS. 6. ALL UNITS TO BE SIZED FOR 30% ETHYLENE GLYCOL CONCENTRATION IN CHILLED WATER. 7. FUSED DISCONNECT. 8. NO ALTERNATE MANUFACTURER'S PERMITTED. UNIT TO BE SOLE-SOURCED TO MATCH EXISTING UNITS AND SYSTEM CURRENTLY PRESENT IN FACILITY.																													

ELECTRIC SUSPENDED UNIT HEATERS (ESUH)																												
EQUIP. TAG		GENERAL										PERFORMANCE						ELECTRICAL						NOTES				
ABB.	NO.	LOCATION	MFR	MODEL	SHIPPING WEIGHT (LBS)	MOUNTING TYPE	LENGTH (IN)	WIDTH (IN)	HEIGHT (IN)	KW	AIRFLOW (CFM)	VOLTS	HZ	PHASE														
ESUH	1	ELEVATOR 12, 13 MACHINE ROOM	KING	KB4803-3	30.5	SUSPENDED	15	11	16.5	3	520	480	60	3	1.2													
ESUH	2	ELEVATOR 11 MACHINE ROOM	KING	KB4805-3	30.5	SUSPENDED	15	11	16.5	5	520	480	60	3	1.2													
ESUH	3	ELEVATOR 1 MACHINE ROOM	KING	KB4805-3	30.5	SUSPENDED	15	11	16.5	5	520	480	60	3	1.2													
ESUH	4	ELEVATOR 12, 13 HOISTWAY	KING	KB4810-3	45	ELEVATOR HOISTWAY WALL	15	13.5	16.5	10	800	480	60	3	2.3.4													
ESUH	5	ELEVATOR 11 HOISTWAY	KING	KB4805-3	30.5	ELEVATOR HOISTWAY WALL	15	11	16.5	5	520	480	60	3	2.3.4													
ESUH	6	ELEVATOR 7,8 HOISTWAY	KING	KB4810-3	45																							



010000. GENERAL NOTES

A. ALL WORK PERFORMED UNDER THIS CONTRACT SHALL BE IN CONFORMANCE WITH ALL GOVERNING NATIONAL, STATE, AND LOCAL CODES HAVING JURISDICTION.

B. ALL EQUIPMENT FURNISHED, AND ALL WORK PERFORMED UNDER THIS CONTRACT SHALL BE IN STRICT COMPLIANCE WITH CURRENT APPLICABLE STANDARDS AS SET FORTH BY THE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA), UNDERWRITERS LABORATORIES (UL), THE AMERICAN GAS ASSOCIATION (AGA), THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME), THE AMERICAN SOCIETY OF HEATING, REFRIGERATING AND AIR CONDITIONING ENGINEERS (ASHRAE), SHEET METAL AND AIR-CONDITIONING CONTRACTORS NATIONAL ASSOCIATION, INC. (SMACNA), AND OTHER NATIONAL STANDARDS WHERE APPLICABLE.

C. CONTRACTOR SHALL REVIEW THE ENTIRE SET OF CONTRACT DOCUMENTS INCLUDING, BUT NOT LIMITED TO, ALL MECHANICAL AND ELECTRICAL DRAWINGS, AS WELL AS ALL SPECIFICATIONS AND INSTRUCTIONS TO BIDDERS. THIS CONTRACTOR SHALL VISIT THE SITE AND MAKE A DETAILED INSPECTION OF THE SPECIFIED WORK TO DEVELOP KNOWLEDGE OF ALL CONDITIONS PERTINENT TO THE COMPLETION OF HIS WORK. THIS CONTRACTOR SHALL FULLY COORDINATE HIS WORK WITH THE WORK PERFORMED BY OTHER TRADES AND/OR CONTRACTORS, AND SHALL MAKE SUCH FIELD ADJUSTMENTS AS ARE REQUIRED TO ACCOMMODATE FIELD CONDITIONS. ALL OF THE ABOVE SHALL BE INCLUDED IN THE SCOPE OF WORK AT NO ADDITIONAL COST TO OWNER.

D. SHOULD CONTRACTOR FIND DISCREPANCIES IN, OR OMISSIONS FROM, THE DRAWINGS, SPECIFICATIONS, OR OTHER CONTRACT DOCUMENTS, OR DISCREPANCIES BETWEEN ACTUAL FIELD CONDITIONS AND THOSE REPRESENTED IN THE DRAWINGS, OR CONFLICTS BETWEEN HIS WORK AND THAT OF OTHER TRADES, OR BE IN DOUBT AS TO THE MEANING OF ANY CONTRACT DOCUMENTS, CONTRACTOR SHALL IMMEDIATELY NOTIFY THE OWNER AND THE ENGINEER IN WRITING AND SHALL OBTAIN A WRITTEN INTERPRETATION FROM THE OWNER AND THE ENGINEER. NO CHANGES SHALL BE CONSTRUED AS CONTRACTOR'S REPRESENTATION THAT NO DISCREPANCIES OR CONFLICTS EXIST. ADDITIONAL COMPENSATION WILL NOT BE GRANTED AFTER AWARD OF CONTRACT FOR ANY WORK REQUIRED TO COMPLY WITH THIS REQUIREMENT.

E. THE DRAWINGS INDICATE DIAGRAMMATICALLY THE INTENT, REQUIREMENTS FOR, AND LOCATION OF THE WORK INCLUDED UNDER THIS CONTRACT. ALL WORK REQUIRED TO AFFECT THE INDICATED DESIGN, INCLUDING DETAILS NOT SHOWN BUT WHOSE INCLUSION WOULD BE DEEMED A REQUIREMENT BY A KNOWLEDGEABLE TRADESMAN, BUILDING ENGINEER, OR TECHNICIAN, SHALL BE PROVIDED AT NO ADDITIONAL COST TO THE OWNER.

F. IT IS THE INTENT OF THESE DOCUMENTS THAT THE CONTRACTOR PROVIDE ALL LABOR, MATERIAL, EQUIPMENT, AND TOOLS FOR THE COMPLETE INSTALLATION OF ALL WORK SHOWN ON THE PLANS AND/OR DESCRIBED HEREIN, INCLUDING ALL DEVICES, CONTROLS, AND APPURTENANCES REQUIRED TO SET THE NEW SYSTEMS INTO OPERATION, UNLESS OTHERWISE NOTED.

G. CONTRACTOR SHALL VERIFY ALL MOUNTING, ARRANGEMENTS, HEIGHTS, AND LOCATIONS PRIOR TO ROUGH-IN. ANY MENTION OF A SPECIFIC MOUNTING ARRANGEMENT, WEIGHT, OR LOCATION SHALL NOT RELIEVE THE CONTRACTOR OF THE RESPONSIBILITY TO VERIFY SPECIFIC REQUIREMENTS AND BASE HIS WORK ON THEM. THE SAME CARE SHALL BE TAKEN WITH RESPECT TO INFORMATION FURNISHED BY THIS CONTRACTOR TO HIS SUBCONTRACTORS OR TO OTHER CONTRACTORS EMPLOYED BY THE OWNER ON THIS PROJECT. THE CONTRACTOR SHALL BE FINALLY RESPONSIBLE FOR ANY CHANGE ORDERS NECESSITATED BY INCORRECT OR INCOMPLETE INFORMATION FURNISHED TO OTHER CONTRACTORS. NO ADDITIONS TO THE CONTRACT AMOUNT WILL BE PERMITTED FOR ITEMS INSTALLED IN WRONG LOCATIONS OR IN CONFLICT WITH OTHER WORK.

H. CONTRACTOR SHALL BE RESPONSIBLE FOR SUBMITTING FOR AND OBTAINING ALL APPLICABLE PERMITS. THIS CONTRACTOR SHALL PAY ALL PERMIT FEES, PLAN REVIEW FEES, LICENSE FEES, AND INSURANCE FEES TO THE APPROPRIATE GOVERNMENTAL AGENCIES. UNLESS OTHERWISE NOTED, THIS CONTRACTOR SHALL ALSO INCLUDE IN HIS BID ALL FEES ASSOCIATED WITH THE SERVICES OF A PERMIT EXPEDITER AS MAY BE REQUIRED TO MEET THE PROJECT SCHEDULE.

I. CONTRACTOR SHALL ESTABLISH SAFE WORKING PROCEDURES FOR THE PROTECTION OF THE WORKMEN IN ALL PHASES OF WORK AND SHALL COMPLY WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL SAFETY LAWS, INCLUDING THE REQUIREMENTS OF OSHA. HE SHALL ALSO PROVIDE ALL NECESSARY SIGNS, LIGHTS, AND BARRICADES REQUIRED FOR THE SAFETY OF ALL OTHER PERSONS WHO MIGHT COME IN CONTACT WITH THE CONSTRUCTION BEING PERFORMED UNDER THIS CONTRACT.

J. ALL PUBLIC AND PRIVATE PROPERTY DAMAGED AS A RESULT OF WORK PERFORMED UNDER THIS CONTRACT SHALL BE REPAIRED AND/OR REPLACED TO MATCH EXISTING CONSTRUCTION BY THIS CONTRACTOR AND TO THE SATISFACTION OF THE OWNER AND AUTHORITIES HAVING JURISDICTION.

K. CONTRACTOR SHALL MAKE ALL ARRANGEMENTS WITH THE BUILDING OWNER'S REPRESENTATIVE REGARDING WORKSITE ACCESS, BUILDING RULES, AND REGULATIONS, INCLUDING WORKING HOURS, REFUSE DISPOSAL, DUMPSTER LOCATION, SECURITY, INTERRUPTIONS OF BUILDING UTILITIES OR FUNCTIONS, OWNERSHIP OF SALVAGED MATERIALS, PARKING, AND ANY OTHER ITEMS DEEMED TO BE OF MUTUAL INTEREST.

L. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO STORE AND PROTECT FROM DAMAGE ALL EQUIPMENT AND MATERIALS IN A MANNER THAT WILL MAINTAIN AN ORDERLY, CLEAN APPEARANCE. DAMAGED EQUIPMENT AND MATERIAL IS SUBJECT TO REJECTION BY THE OWNER'S REPRESENTATIVE. REPLACEMENT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.

M. PROVIDE ALL HOLES, SLEEVES, CUTTING, PATCHING, AND SEALING FOR INSTALLATION OF THIS WORK. SEALING SHALL CONFORM TO THE FIRE RATING OF ALL BUILDING ASSEMBLIES. ALL EXTERIOR PENETRATIONS SHALL BE MADE WEATHER TIGHT.

N. CONTRACTOR IS RESPONSIBLE FOR LOCATING, INCLUDING SCANNING WHERE NECESSARY, OBSTRUCTIONS/REINFORCEMENTS WHERE PENETRATIONS ARE TO BE MADE. ANY DAMAGE RESULTING FROM PENETRATIONS IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND SHALL BE REPAIRED AT NO ADDITIONAL COST TO THE OWNER.

O. CONTRACTOR SHALL NOT MODIFY OR REMOVE ANYTHING FOUND TO BE IN THE PATH OF NEW SYSTEMS TO BE INSTALLED WITHOUT PRIOR APPROVAL BY THE ENGINEER.

P. THE CONTRACTOR IS RESPONSIBLE FOR THE CONTINUOUS CLEANING OF ALL DUST AND DEBRIS RESULTING FROM THEIR WORK.

Q. CONTRACTOR TO DETERMINE REQUIRED SYSTEM SHUTDOWNS. MAXIMUM DURATION OF SYSTEM SHUTDOWN SHALL BE AT THE DISCRETION OF THE OWNER'S REPRESENTATIVE. SHUTDOWN SHALL BE COORDINATED ON THE JOB SITE WITH THE OWNER'S REPRESENTATIVE. CONTRACTOR SHALL PROVIDE A MINIMUM OF ONE (1) WEEK ADVANCE NOTICE OF SYSTEM SHUTDOWNS.

R. CONTRACTOR SHALL BE PROPERLY LICENSED, BONDED, AND INSURED AND CAPABLE OF PERFORMING QUALITY WORKMANSHIP ON THIS PROJECT.

S. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, AND SAFETY.

T. REMOVAL AND RESTORATION OF FINISHED SURFACES AS REQUIRED TO COMPLETE THIS SCOPE OF WORK IS THE RESPONSIBILITY OF THIS CONTRACTOR.

U. CONTRACTOR SHALL COORDINATE USE OF THE BUILDING ELEVATOR(S) AND DELIVERIES WITH THE OWNER.

V. MAINTAIN ALL MANUFACTURER RECOMMENDED AND CODE REQUIRED CLEARANCES.

W. CONTRACTOR SHALL PROVIDE TRAINING TO THE OPERATING STAFF FOR NEW SYSTEMS AND EQUIPMENT. REFER TO OWNER TRAINING SPECIFICATION SECTION FOR ADDITIONAL INFORMATION.

010002. OWNER TRAINING

A. THE CONTRACTOR SHALL PROVIDE DEMONSTRATION AND TRAINING TO OWNER'S PERSONNEL FOR NEW SYSTEMS AND EQUIPMENT. THE COSTS ASSOCIATED WITH THIS SHALL BE INCLUDED AS PART OF THE BASE BID UNLESS OTHERWISE NOTED.

B. ALL EQUIPMENT MANUALS, INSTALLATION OPERATION AND MAINTENANCE MANUALS, ETC. SHALL BE TURNED OVER TO THE OWNER PRIOR TO COMMENCING OWNER DEMONSTRATION AND TRAINING. REFER TO PROJECT CLOSEOUT DOCUMENT REQUIREMENTS FOR ADDITIONAL INFORMATION.

C. CONTRACTOR SHALL PROVIDE A MINIMUM OF 4 HOURS OF TRAINING OVER 1 VISITS ON SITE FOR OWNER PERSONNEL.

D. OWNER TRAINING SHALL BE CONDUCTED AFTER FUNCTIONAL TESTING IS COMPLETE AS APPROVED BY THE ENGINEER AND (WHERE APPLICABLE) COMMISSIONING AUTHORITY.

E. COORDINATE TRAINING WITH OWNER, ENGINEER & COMMISSIONING AUTHORITY.

013000. SHOP DRAWINGS, SUBMITTALS, AND AS-BUILTS

A. CONTRACTOR SHALL SUBMIT TO THE ENGINEER COORDINATED SHOP DRAWINGS. SHOP DRAWINGS SHALL BE 1/4 SCALE AND SHALL INDICATE LAYOUT OF ALL EQUIPMENT, DUCTS, PIPING, THERMOSTATS, SENSORS, GRAPHICS, CONTROLS, NETWORK ARCHITECTURE, CONTROL POINTS LIST, OPERATING SEQUENCES, CONTROL DEVICES WITH SETTINGS OR ADJUSTABLE RANGES, ETC. SHOP DRAWINGS SHALL INCLUDE ALL DUCT AND PIPE SIZES, CAPACITIES, ELEVATIONS, ETC. CONTRACTOR SHALL PROCEED WITH SITE WORK ONLY AFTER RECEIVING SHOP DRAWINGS MARKED REVIEWED.

1. SHOULD CONDITIONS NECESSITATE ANY REARRANGEMENTS, CONTRACTOR SHALL SUBMIT TO THE ENGINEER SHOP DRAWINGS SHOWING SUCH CHANGES. CONTRACTOR SHALL PROCEED WITH SITE WORK ONLY AFTER RECEIVING SHOP DRAWINGS MARKED REVIEWED.

B. CONTRACTOR SHALL SUBMIT TO THE ENGINEER MANUFACTURERS' SUBMITTALS FOR ALL EQUIPMENT AND ACCESSORIES. CONTRACTOR SHALL PROCEED WITH PROCUREMENT ONLY AFTER RECEIVING SUBMITTALS MARKED REVIEWED.

C. CONTRACTOR SHALL SUBMIT THE FOLLOWING ELECTRONIC FILES TO THE ENGINEER AND OWNER AS PART OF THE CLOSEOUT PACKAGE:

1. ALL APPROVED SUBMITTALS, INCLUDING FINAL EQUIPMENT DATA SHEETS, CONTROL SEQUENCES, AND APPROVED SHOP DRAWINGS REFLECTING THE INSTALLED SYSTEMS.

2. OPERATION AND MAINTENANCE MANUALS (IOMs), INCLUDING INSTALLATION INSTRUCTIONS, ROUTINE AND PREVENTIVE MAINTENANCE PROCEDURES, TROUBLESHOOTING GUIDES, AND PARTS LISTS FOR ALL MAJOR EQUIPMENT.

3. AS-BUILT DRAWINGS, INCLUDING RECORD LOCATIONS OF CONTROL COMPONENTS, INCLUDING CONTROL UNITS, THERMOSTATS, AND SENSORS. REVISE SHOP DRAWINGS TO REFLECT ACTUAL INSTALLATION AND OPERATING SEQUENCES.

4. FINAL ENGINEERING DRAWINGS FOR ALL DISCIPLINES.

5. COMMISSIONING AND FUNCTIONAL TESTING REPORTS (AS APPLICABLE). DOCUMENT SYSTEM START UP, TESTING, ADJUSTING, AND BALANCING RESULTS.

6. PUNCH LIST DOCUMENTATION AND COMPLETED SIGN OFFS, INCLUDING SIGNED CONFIRMATION THAT ALL PUNCH LIST ITEMS HAVE BEEN ADDRESSED AND RESOLVED.

7. WARRANTY DOCUMENTATION, INCLUDING MANUFACTURER, PRIME CONTRACTOR AND SUB-CONTRACTOR WARRANTIES, CLEARLY IDENTIFYING COVERAGE PERIODS, TERMS, AND START DATES.

8. TRAINING DOCUMENTATION, INCLUDING TRAINING AGENDAS, PRESENTATION MATERIALS, AND SIGN-IN SHEETS VERIFYING OWNER PERSONNEL'S PARTICIPATION.

9. PERMIT CLOSEOUT AND INSPECTION CERTIFICATES.

10. COST SUMMARY AND FINAL PAY APPLICATIONS.

11. VENDOR AND SUBCONTRACTOR CONTACT INFORMATION, INCLUDING NAMES, PHONE NUMBERS, EMAIL ADDRESSES, AND EMERGENCY CONTACTS.

013001. MATERIALS AND EQUIPMENT

A. ALL MATERIALS AND EQUIPMENT INSTALLED UNDER THIS CONTRACT SHALL BE NEW, UNLESS OTHERWISE STATED IN THESE CONTRACT DOCUMENTS, AND FREE FROM DEFECTS.

B. ALL MATERIALS AND EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURERS' RECOMMENDATIONS.

C. CONTRACTOR IS REQUIRED TO REVIEW ALL DRAWINGS. MATERIALS AND EQUIPMENT SHOWN ON THE SCHEDULES AND DETAILS SHALL BE INCLUDED IN BASE BID. NO MATERIAL OR EQUIPMENT SUBSTITUTIONS WILL BE CONSIDERED AFTER THE AWARD OF CONTRACT. IF CONTRACTOR DESIRES TO SUBSTITUTE MATERIAL OR EQUIPMENT, CONTRACTOR MUST SUBMIT AS ALTERNATE WITH HIS BASE BID A LIST OF SUCH ITEMS INDICATING ITEM, MANUFACTURER, MODEL NUMBER, AND AMOUNT TO BE ADDED TO OR DEDUCTED FROM THE BASE BID. EACH SUCH MATERIAL OR EQUIPMENT SUBSTITUTION ITEM SHALL BE LISTED SEPARATELY.

D. CONTRACTOR SHALL BE RESPONSIBLE FOR SCHEDULING THE PURCHASE, DELIVERY, RECEIVING, UNLOADING, UNCRATING, STORING, SETTING IN PLACE, AND PROTECTING OF ALL NEW EQUIPMENT FURNISHED BY THE CONTRACTOR OR PROVIDED TO THE CONTRACTOR BY THE OWNER, AND SHALL SECURE SUCH EQUIPMENT FROM DAMAGE UNTIL TIME OF FINAL ACCEPTANCE BY THE OWNER.

E. CONTRACTOR SHALL FURNISH AND INSTALL ALL STRUCTURE, SLEEVES, SHIMS, ETC. REQUIRED TO LEVEL AND SUPPORT EQUIPMENT AND MATERIALS. INSTALL NONMETALLIC NON-SHRINK GROUT FOR LEVELING EQUIPMENT BASES.

F. CONTRACTOR SHALL VERIFY ALL PHYSICAL, ELECTRICAL, INGRESS, ETC. REQUIREMENTS FOR ALL EQUIPMENT PRIOR TO ORDERING.

G. CONTRACTOR SHALL SUBMIT TO OWNER THE PROPOSED LABELS/IDENTIFICATION PRODUCT FOR EACH PIECE OF EQUIPMENT PRIOR TO ORDERING. EQUIPMENT LABELS/IDENTIFICATION SHALL CONFORM TO THE FOLLOWING:

1. MATERIAL AND THICKNESS: MULTILAYER, MULTICOLOR, PLASTIC LABELS FOR MECHANICAL ENGRAVING, 1/8 INCH THICK, AND HAVING PREDRILLED HOLES FOR ATTACHMENT HARDWARE.
2. LETTER COLOR: WHITE.
3. BACKGROUND COLOR: BLUE.
4. MAXIMUM TEMPERATURE: ABLE TO WITHSTAND TEMPERATURES UP TO 160 DEG F.
5. MINIMUM LABEL SIZE: LENGTH AND WIDTH VARY FOR REQUIRED LABEL CONTENT, BUT NOT LESS THAN 2-1/2 INCH BY 3/4 INCH.
6. MINIMUM LETTER SIZE: 1/4 INCH FOR NAME OF UNITS IF VIEWING DISTANCE IS LESS THAN 24 INCHES; 1/2 INCH FOR VIEWING DISTANCES UP TO 72 INCHES, AND PROPORTIONATELY LARGER LETTERING FOR GREATER VIEWING DISTANCES. INCLUDE SECONDARY LETTERING TWO-THIRDS TO THREE-FOURTHS THE SIZE OF PRINCIPAL LETTERING.
7. FASTENERS: STAINLESS-STEEL RIVETS OR SELF-TAPPING SCREWS.
8. ADHESIVE/CONTACT-TYPE PERMANENT ADHESIVE, COMPATIBLE WITH LABEL AND WITH SUBSTRATE.
9. EQUIPMENT DATA, LABELS, AND OTHER IDENTIFICATION SHALL NOT BE OBSTRUCTED.
10. CONTRACTOR SHALL PROVIDE FILTERS, STRAINER SCREENS, ETC. FOR ALL NEW EQUIPMENT DURING CONSTRUCTION. REPLACE FILTERS, STRAINERS SCREENS, ETC. WITH FINAL FILTERS, STRAINER SCREENS, ETC. AT COMPLETION OF PROJECT AND PRIOR TO TEST AND BALANCE.

017400. WARRANTY

A. SEE BID DOCUMENTS.

020000. GENERAL DEMOLITION NOTES

A. ALL WORK SHALL BE PERFORMED IN A CLEAN AND WORKMANLIKE MANNER. CARE SHALL BE EXERCISED TO MINIMIZE ANY INCONVENIENCE OR DISTURBANCE TO OTHER AREAS OF THE BUILDING, WHICH ARE TO REMAIN IN OPERATION.

B. ALL DEMOLITION AS CALLED FOR ON THE DEMOLITION DRAWINGS SHALL BE UNDER THIS CONTRACTOR'S WORK.

C. CONTRACTOR SHALL VISIT THE BUILDING BEFORE SUBMITTING HIS BID, TO VERIFY ALL DIMENSIONS AND EXISTING CONDITIONS WHICH MAY AFFECT HIS WORK. NOT ALL EXISTING DUCTWORK, PIPING, EQUIPMENT, ETC. MAY BE INDICATED ON DOCUMENTS.

D. THE INTENT OF THE DEMOLITION IS TO REMOVE THE ITEMS IN THEIR ENTIRETY. THIS INCLUDES ALL ASSOCIATED SUPPORT BASES, ANCHORAGE, HANGERS, CONTROLS INCLUDING WIRING AND CONDUIT EXPOSED IN MECHANICAL ROOMS, PIPING, DUCTWORK, WIRING, ETC. CAP EXISTING SYSTEMS TO REMAIN AT MAINS OR OTHER ACTIVE BRANCH LINES. MINIMIZE DEAD END LENGTHS. LABEL ABANDONED CONTROLS CONDUIT AND WIRE.

E. BEFORE STARTING ANY DEMOLITION WORK ON EQUIPMENT WHICH HAS AN ELECTRICAL CONNECTION, THE ELECTRICAL CONTRACTOR SHALL DISCONNECT THE POWER AND REMOVE CONDUIT, WIRING, DISCONNECT SWITCHES, AND STARTERS UNDER THIS CONTRACT.

F. CONTRACTOR SHALL BE RESPONSIBLE FOR CONTINUOUS CLEANUP THROUGHOUT THE COURSE OF THE DEMOLITION WORK.

G. ALL EQUIPMENT, MATERIAL, ETC. THAT IS DEMOLISHED SHALL BE REMOVED FROM THE BUILDING SITE BY THIS CONTRACTOR IN A PROPER AND LEGAL MANNER. NO ITEM WHICH IS DEMOLISHED MAY BE REUSED UNLESS SPECIFICALLY NOTED.

H. ANY CONTROLS HARDWARE OR PROGRAMMING NO LONGER NECESSARY TO ACCOMPLISH THE SEQUENCE OF OPERATIONS SHALL BE DECOMMISSIONED.

I. ALL DEMOLITION WORK OF THE EXISTING CONTROLS FOR EQUIPMENT SHOWN ON THE DRAWINGS TO BE DEMOLISHED SHALL BE THE RESPONSIBILITY OF THIS CONTRACTOR. THIS CONTRACTOR SHALL MODIFY THE EXISTING CONTROLS AS REQUIRED TO ENSURE OPERATION OF EXISTING EQUIPMENT TO REMAIN. ALL EXISTING CONTROLS SHOWN TO BE DEMOLISHED SHALL BE REMOVED AND TURNED OVER TO THE OWNER.

230593. TESTING AND BALANCING

A. UPON SUBSTANTIAL COMPLETION OF SYSTEMS INSTALLATION, AND PRIOR TO ACCEPTANCE BY THE ENGINEER AND OWNER, THIS CONTRACTOR SHALL SUBCONTRACT A TAB CONTRACTOR WHO'S TECHNICIANS ARE NEBB OR AABC CERTIFIED. TAB SUBCONTRACTOR SHALL NOT BE AFFILIATED WITH THE CONTRACTOR.

B. TEST PROCEDURES SHALL BE PER LATEST EDITIONS OF NEBB, AABC, OR TESTING, ADJUSTING, AND BALANCING CHAPTER OF ASHRAE APPLICATIONS HANDBOOK.

C. PRIOR TO ALL TAB PROCEDURES PROCEEDING, SYSTEMS INSTALLATION, STARTUP, AND OPERATION SHALL BE IN ACCORDANCE WITH THE CONTRACT DOCUMENTS AND PER THE MINIMUM REQUIREMENTS OF NEBB, AABC, OR ASHRAE. IF DEFICIENCIES ARE FOUND WHICH PREVENT PROPER TAB PROCEDURES AND REPEATABLE RESULTS, THIS CONTRACTOR SHALL BE RESPONSIBLE FOR ALL RESULTING COSTS.

D. THE OWNER, ENGINEER, AND COMMISSIONING AUTHORITY SHALL BE NOTIFIED WHEN TAB SCOPE WILL BEGIN ON SITE, AUTHORIZED REPRESENTATIVE OF THE OWNER MAY BE IN ATTENDANCE IF DEEMED NECESSARY.

E. THIS CONTRACTOR TO ASSIST THE TAB CONTRACTOR AS REQUIRED TO ENSURE REPEATABLE RESULTS. THIS CONTRACTOR SHALL PROVIDE THE TAB CONTRACTOR WITH ALL REQUIRED DOCUMENTATION TO SUPPORT TAB SCOPE.

F. TAB CONTRACTOR SCOPE SHALL INCLUDE ALL NEW SYSTEMS AND EQUIPMENT INCLUDING AIR FLOW STATIONS AND BTU METERS.

G. TAB CONTRACTOR SCOPE SHALL INCLUDE EXISTING SYSTEMS AS IDENTIFIED IN THE DOCUMENTS OR AS REQUIRED FOR A FULLY FUNCTIONAL AND FULLY BALANCED SYSTEM.

H. TAB CONTRACTOR SHALL PROVIDE A SUBMITTAL PRIOR TO PERFORMING ANY WORK FOR REVIEW BY THE ENGINEER INCLUDING THE FOLLOWING:

1. TAB PERSONNEL QUALIFICATION AND CERTIFICATION REPORTS.
2. TEST PROCEDURES SPECIFIC TO THIS PROJECT.
3. TEST FORMS SPECIFIC TO THIS PROJECT INCLUDING FAN CURVES.
4. TAB CONTRACTOR SHALL PROVIDE REPORT IN ACCORDANCE WITH UTILIZED STANDARD ALONG WITH AN EXECUTIVE SUMMARY STATING THE EXTENT OF SYSTEM COMPLIANCE, SYSTEM DEFICIENCIES, AND RECOMMENDED CHANGES. THIS REPORT SHALL BE SUBMITTED WITHIN THIRTY (30) DAYS OF COMPLETION OF THIS SCOPE OF WORK.
5. TAB CONTRACTOR SHALL COORDINATE WITH THE BASC AS REQUIRED TO PERFORM SCOPE OF WORK, DETERMINE CONTROL SETPOINTS, ETC. FOR PROPER OPERATION OF THE SYSTEM.
6. ALL BALANCING PROCEDURES SHALL BE PERFORMED TO MINIMIZE ENERGY USAGE.

232113. PIPING

A. GENERAL

1. COMPLY WITH PROVISIONS OF ASME B31.
2. SYSTEM COMPONENTS WHICH REQUIRE OBSERVATION, OPERATION, OR MAINTENANCE, SUCH AS VALVES, CONTROLS, STRAINERS, CLEANOUTS, ETC. SHALL BE READILY ACCESSIBLE. THEY SHALL NOT BE CONCEALED IN CHASES OR ABOVE CEILINGS WITHOUT PROVISION FOR ACCESS. VALVES WHICH ARE NOT ACCESSIBLE FROM NORMAL WORKING LEVEL SHALL BE INSTALLED WITH CHAIN WHEELS OR EXTENSIONS.
3. INSTALL PIPING TO PERMIT COMPLETE SYSTEM DRAINING.
4. INSTALL EQUIPMENT AND MATERIALS HAVING PRESSURE RATING EQUAL TO OR GREATER THAN MAXIMUM SYSTEM PRESSURE.
5. INSTALL INTERIOR PIPING AT RIGHT ANGLES OR PARALLEL TO BUILDING WALLS. DIAGONAL RUNS ARE PROHIBITED, EXCEPT WHERE INDICATED OR APPROVED PRIOR TO INSTALLATION.
6. INSTALL PIPING TO ALLOW APPLICATION OF INSULATION PLUS 1-INCH CLEARANCE AROUND INSULATION.

B. PRESSURE TESTING

1. SUBJECT ALL NEW HYDROSTATIC PIPING TO HYDROSTATIC PRESSURE TESTS THAT IS NOT LESS THAN 50 PSIG AND 1.5 TIMES THE SYSTEM'S WORKING PRESSURE FOR A MINIMUM OF 4 HOURS OR AS SPECIFICALLY INDICATED. TEST PRESSURE SHALL NOT EXCEED MAXIMUM PRESSURE RATING FOR ANY VESSEL, PUMP, VALVE, OR OTHER COMPONENT IN SYSTEM UNDER TEST. SUBMIT REPORT WITHIN 48 HOURS OF TEST DATE TO ENGINEER INDICATING TEST DATE, TEST PRESSURE, AND DURATION, AS WELL AS CERTIFICATION OF SUCCESSFUL TEST.
2. PIPING SHALL NOT BE CONCEALED, INSULATED, OR SIMILAR UNTIL PRESSURE TESTING IS COMPLETE AND REVIEWED.

C. HYDROSTATIC PIPING ABOVE GRADE

1. FOR SIZES 2" AND SMALLER, ALL NEW ABOVE GRADE HYDROSTATIC PIPING SHALL BE SCHEDULE 40 BLACK STEEL PIPE WITH MALLEABLE IRON SCREWED FITTINGS OR TYPE L COPPER WITH 95% SOLDERED JOINTS.
2. FOR SIZES 2-1/2" AND LARGER, ALL NEW ABOVE GRADE HYDROSTATIC PIPING SHALL BE SCHEDULE 40 STANDARD WEIGHT, A33, TYPE E, GRADE B BLACK STEEL PIPE WITH WELDED PIPE AND FITTINGS OR TYPE L COPPER WITH 95% SOLDERED JOINTS.
3. MECHANICAL FITTINGS WILL NOT BE ALLOWED. MECHANICAL FITTINGS MAY BE BID AS AN ALTERNATE WHERE EXPOSED AND ACCESSIBLE IN MECHANICAL ROOMS.

D. COOLING CONDENSATE DRAIN PIPING

1. ALL NEW COOLING CONDENSATE DRAIN PIPING SHALL BE TYPE 'M' COPPER WITH SOLDERED JOINTS.

E. HYDROSTATIC PIPING INSULATION

1. FURNISH AND INSTALL ALL NEW PIPING, VALVES, FITTINGS, ETC. AND EXISTING PIPING AS INDICATED ON THE DOCUMENTS WITH FIBERGLASS MOLED PIPE INSULATION APPLIED WITH AN ALL-SERVICE VAPOR BARRIER JACKET, STAPLED, WITH THE SEAMS, JOINTS, AND STAPLES PAINTED WITH VAPOR-PROOF MASTIC.
2. ALL DAMAGED INSULATION (RESULTING FROM IMPLEMENTATION OF THIS PROJECT) ON EXISTING PIPING TO REMAIN SHALL BE REPLACED.
3. MINIMUM INSULATION THICKNESS SHALL BE IN ACCORDANCE WITH THE FOLLOWING SCHEDULE AND ALL APPLICABLE CODES:
 - a. CHILLED WATER: 1"
 - b. CONDENSATE DRAIN PIPING: 1/2"
4. VAPOR BARRIER JACKET SHALL HAVE FACTORY-APPLIED VAPOR RETARDER COMPOSED OF A WHITE KRAFT FACING REINFORCED WITH GLASS FIBER YARN AND BONDED TO ALUMINIZED FILM. LAM ADHESIVE SHALL BE COMPATIBLE WITH INSULATION.
5. FURNISH AND INSTALL PVC COVERS FOR ALL VALVES AND ALL PIPE FITTINGS.

F. PIPING VALVES

1. INSTALL ALL VALVES WITH STEMS IN EITHER AN UPRIGHT (PREFERRED) OR HORIZONTAL POSITION. CONTROL VALVES SHALL BE INSTALLED WITH ACTUATOR UPWARD UNLESS NOTED OTHERWISE OR REQUIRED FOR MAINTENANCE.
2. ISOLATION VALVES SHALL BE ANSI/FCI 70-2006 CLASS VI, RATED FOR ZERO LEAKAGE.
3. INSTALL BRANCH ISOLATION VALVES AT EACH BRANCH TAKE-OFF FROM THE MAIN. BRANCH ISOLATION VALVES ARE TO BE IN ADDITION TO EQUIPMENT ISOLATION VALVES UNLESS APPROVED BY THE ENGINEER.
4. BALL VALVES (2 NPS AND SMALLER)
 - a. 2 PIECE BRONZE BODY 600 WOG RATED, FULL PORT
 - b. CHROME PLATED BRONZE BALL
 - c. 2-1/4" VALVE EXTENSION
 - d. TEFLOON SEAT AND STUFFING BOX RING
 - e. LEVER HANDLE WITH BALANCE STOPS
 - f. ACCEPTABLE MANUFACTURERS:
 - i. APOLLO, NIBCO, MILWAUKEE
5. SWING CHECK VALVE (2 NPS AND SMALLER)
 - a. BRONZE BODY, BRONZE TRIM, BRONZE ROTATING SWING DISC
 - b. COMPOSITE DISC
 - c. TREADED ENDS
 - d. ACCEPTABLE MANUFACTURERS:
 - i. APOLLO, NIBCO, MILWAUKEE
6. BALANCING VALVES (UP TO AND INCLUDING 2")
 - a. BRASS COPPER ALLOY OR BRONZE BODY/BRASS BALL CONSTRUCTION
 - b. GLASS AND CARBON FILLED TEE SEAT RINGS
 - c. ACCEPTABLE MANUFACTURERS:
 - i. ARMSTRONG, B&G, TACO, T&A

G. PIPING ACCESSORIES

1. STRAINERS (UP TO AND INCLUDING 2")
 - a. SCREWED BRASS OR IRON BODY
 - b. Y PATTERN WITH 1/32" STAINLESS STEEL PERFORATED SCREEN
 - c. ACCEPTABLE MANUFACTURERS:
 - i. KECKLEY, WATTS, APOLLO, NIBCO, MILWAUKEE
2. AIR VENTS
 - a. MANUAL TYPE: SHORT VERTICAL SECTIONS OF PIPE TO/FROM AIR CHAMBER, WITH 1/8" BRASS NEEDLE VALVE AT TOP OF CHAMBER
 - b. FLOAT TYPE: BRASS OR SEMI-STEEL BODY, COPPER, STAINLESS STEEL VALVE AND SEAT; SUITABLE FOR SYSTEM OPERATING TEMPERATURE AND PRESSURE; WITH ISOLATING VALVE
 - c. WASHER TYPE: BRASS WITH HYDROSCOPIC FIBER DISCS, VENT PORTS, ADJUSTABLE CAP FOR MANUAL SHUT-OFF, AND INTEGRAL SPRING LOADED BALL CHECK VALVE.
 - d. ACCEPTABLE MANUFACTURERS:
 - i. BELL AND GOSETT, TACO, ARMSTRONG
3. REDUCERS
 - a. UNLESS OTHERWISE SHOWN ON THE DRAWINGS, INSTALL ALL SUPPLY PIPING TO COILS, PUMPS, AND OTHER EQUIPMENT INCLUDING VALVES AND STRAINERS THEREIN, AT LINE SIZE IF A REDUCTION IS REQUIRED AT A PUMP, COIL, CONTROL VALVE, ETC. THE REDUCER SHALL BE LOCATED AS CLOSE AS POSSIBLE TO THE DEVICE.
 - b. USE ECCENTRIC REDUCING FITTINGS OR ECCENTRIC REDUCING COUPLINGS WHERE REQUIRED TO PREVENT POCKETING OF LIQUID.
 - c. WHERE ECCENTRIC REDUCERS ARE USED, THE STRAIGHT SIDE SHOULD BE INSTALLED ON TOP FOR PUMP SUCTION AND ON THE BOTTOM FOR ALL OTHER LINES.
4. INSTALL AIR VENTS AT HIGH POINTS IN ALL PIPING ANS AS REQUIRED FOR SYSTEM VENTING.
5. INSTALL DRAIN VALVES AT LOW POINTS IN PIPING AND AS REQUIRED FOR SYSTEM DRAINAGE. DRAINS SHALL NOT BE LESS THAN 3/4".
6. INSTALL UNIONS IN PIPING 2 INCHES AND SMALLER ADJACENT TO EACH VALVE AND AT FINAL CONNECTION TO EACH PIECE OF EQUIPMENT HAVING A 2-INCH OR SMALLER THREADED PIPE CONNECTION.
7. INSTALL DI-ELECTRIC FITTINGS TO CONNECT PIPING MATERIALS OF DISSIMILAR METALS.

ISSUE/REVISION:
 REV DATE DESCRIPTION
 1/30/2026 ISSUED FOR BID

PROJECT: RATE FIELD - HVAC FY2026


333 WEST 35TH STREET
 CHICAGO, IL 60616

DRAWING TITLE: MECHANICAL SPECIFICATIONS

DESIGNED BY: MO
 CHECKED BY: CC
 PROJECT NO: 25080
 SCALE: NO SCALE
 SHEET NO.</



AHU BAS KEYED NOTES	
1.	DAMPER TO REMAIN BASIC TO FURNISH AND INSTALL REPLACEMENT ACTUATOR AND ENSURE PROPER OPERATION OF DAMPER. (AHU-5B-3 AND AHU-7D-1 ONLY)
2.	DAMPER TO REMAIN BASIC TO FURNISH AND INSTALL REPLACEMENT ACTUATOR AND ENSURE PROPER OPERATION OF DAMPER. (MECHANICAL ROOMS 6.30.5 AND 7.29.1 ONLY)
3.	BASC SHALL PROVIDE TWO-WAY MODULATING CONTROL VALVE FOR AHU COOLING COIL. MC TO INSTALL. BASC RESPONSIBLE FOR ALL LOW VOLTAGE WIRING AND RACEWAYS. EACH CONTROL VALVE SHALL HAVE 24 VOLT ACTUATORS AND SHALL BE CONFIGURED TO FAIL CLOSED ON LOSS OF POWER AND ON LOSS OF CONTROL SIGNAL SO THAT CONTROL VALVE CLOSES IF CONDENSATE OVERFLOW SWITCH IS ACTIVATED. PROVIDE PRESSURE INDEPENDENT CONTROL VALVES (PICVS) THAT CAN BE FIELD ADJUSTED ABOVE AND BELOW THE FLOW RATES SPECIFIED IN THIS SCHEDULE. VALVE TO BE SELECTED SO THAT THE SPECIFIED FLOW RATE FALLS WITHIN THE MIDDLE OF THE CONTROL VALVE FLOW RANGE. CONTROL VALVES TO HAVE MINIMUM ANSI CLASS OF 125 AND MINIMUM 100PSI CLOSE OFF PRESSURE RATING. CONTROL VALVE SHALL INCLUDE BRASS TRIM AND STAINLESS STEEL STEM. EACH VALVE SHALL INCLUDE THE P/T TEST POINT OPTION.
4.	BASC TO PROVIDE SUPPLY AIR TEMPERATURE SENSOR. TEMPERATURE SENSOR PROBE LENGTH TO BE SIZED SO THAT IT READS IN THE CENTER OF THE DUCTWORK.
5.	BASC TO PROVIDE SPACE TEMPERATURE SENSORS AND ADD POINTS TO BAS FOR EACH AHU. REFER TO FLOOR PLANS FOR APPROXIMATE SENSOR LOCATIONS; COORDINATE FINAL LOCATION WITH OWNER. PROVIDE TEMPERATURE SENSOR WITH FLAT-PLATE FACE.
6.	BASC TO PROVIDE HUMIDITY SENSOR. COMBINATION SENSOR IS ACCEPTABLE.
7.	BASC TO FURNISH AND INSTALL FREEZESTAT.



1 AIR HANDLING UNIT - CONTROLS SCHEMATIC

SCALE: NO SCALE


AHU SEQUENCE OF OPERATION

1. SYSTEM DESCRIPTION
 - A. APPLIES TO INDOOR AIR HANDLERS SERVING ELEVATOR MACHINE ROOMS. THE AHUS ARE EQUIPPED WITH THE FOLLOWING:
 - a. OUTSIDE AIR DAMPER (WHERE INDICATED)
 - b. RETURN AIR DAMPER (WHERE INDICATED)
 - c. CHILLED WATER COOLING COIL WITH MODULATING VALVE
 - d. ELECTRIC HEATING COIL
 - e. CONSTANT VOLUME SUPPLY FAN
 - f. REMOTE SPACE TEMPERATURE SENSOR AND SPACE HUMIDITY SENSOR
2. SCHEDULING:
 - A. THE AHU SHALL OPERATE YEAR-ROUND AS REQUIRED TO MAINTAIN SPACE CONDITIONS.
 - B. NO UNOCCUPIED MODE SHALL BE USED. NO NIGHT SETBACK SHALL APPLY.
3. UNIT START-UP:
 - A. THE AHU SHALL ENABLE WHEN ANY OF THE FOLLOWING CONDITIONS ARE TRUE:
 - a. SPACE TEMPERATURE IS BELOW 50°F (ADJ.)
 - b. SPACE TEMPERATURE IS ABOVE 80°F (ADJ.)
 - c. SPACE HUMIDITY IS ABOVE 80% RH (ADJ.)
 - d. THE BAS IS MANUALLY ENABLED
 - B. UPON ENABLING, CONFIRM THE FOLLOWING CONDITIONS PRIOR TO START:
 - a. CHILLED WATER PUMP IS AVAILABLE (IF COOLING IS REQUIRED)
 - b. DISCHARGE AIR TEMPERATURE (DAT) SENSOR IS READING VALID VALUES.
 - C. AHU START SEQUENCE:
 - a. SUPPLY FAN SHALL START.
 - b. OUTSIDE AIR AND RETURN AIR DAMPERS SHALL DRIVE TO OCCUPIED/MINIMUM POSITIONS.
 - c. HEATING AND COOLING CONTROL LOOPS SHALL BE ENABLED.
4. UNIT SHUTDOWN:
 - A. UNIT SHALL SHUT DOWN ONLY IF:
 - a. A SAFETY TRIP OCCURS, OR
 - b. THE BAS IS MANUALLY COMMANDED OFF FOR SERVICE.
 - B. UPON SHUTDOWN, DAMPERS SHALL CLOSE AND SUPPLY FAN SHALL STOP.
5. FAN CONTROL:
 - A. SUPPLY FAN SHALL OPERATE CONTINUOUSLY WHEN THE AHU IS ENABLED.
6. COOLING CONTROL - CHILLED WATER COIL:
 - A. THE CHILLED WATER CONTROL VALVE SHALL MODULATE TO MAINTAIN THE SPACE TEMPERATURE COOLING SETPOINT (68°F MAX. ADJ.)
 - B. THE VALVE SHALL MODULATE OPEN AS THE SPACE TEMPERATURE RISES ABOVE SETPOINT AND MODULATE CLOSED AS THE SPACE TEMPERATURE FALLS BELOW SETPOINT.
7. HEATING CONTROL - ELECTRIC HEATING COIL:
 - A. ELECTRIC HEATING SHALL BE ENABLED WHEN THE SPACE TEMPERATURE FALLS BELOW 50°F (ADJ.).
 - B. ELECTRIC HEATING SHALL DE-ENERGIZE WHEN THE SPACE TEMPERATURE SETPOINT (50°F MINIMUM) IS SATISFIED.
 - C. HIGH-TEMPERATURE CUTOUT SHALL TRIP HEAT AND GENERATE AN ALARM.
8. VENTILATION CONTROL - OA/RA DAMPERS:
 - A. OUTSIDE AIR DAMPER SHALL MAINTAIN A MINIMUM POSITION FOR VENTILATION.
 - B. RETURN AIR DAMPER SHALL MODULATE IN SEQUENCE WITH OUTSIDE AIR DAMPER.
 - C. DAMPERS SHALL CLOSE ONLY ON MANUAL SYSTEM SHUTDOWN OR SAFETY TRIP.
9. HUMIDITY MONITORING:
 - A. BAS SHALL MONITOR SPACE RELATIVE HUMIDITY.
 - B. HIGH HUMIDITY ALARM SHALL BE GENERATED WHEN SPACE HUMIDITY EXCEEDS 80% RH (ADJ.) FOR 10 MINUTES (ADJ.).
10. GRAPHICS:
 - A. DISPLAY THE FOLLOWING ON THE BAS GRAPHICS:
 - a. SPACE TEMPERATURE
 - b. SPACE HUMIDITY
 - c. DISCHARGE AIR TEMPERATURE
 - d. COOLING VALVE POSITION
 - e. OA/RA DAMPER POSITIONS
11. ALARMS:
 - A. CRITICAL ALARMS SHALL BE ANNUNCIATED AT THE OPERATOR WORKSTATION AND EMAILED TO THE OWNER.
 - a. CRITICAL ALARMS SHALL INCLUDE:
 - SPACE TEMPERATURE BELOW 50°F (ADJ.)
 - SPACE TEMPERATURE ABOVE 90°F (ADJ.)
 - SPACE HUMIDITY ABOVE 80% RH (ADJ.)
 - HIGH-TEMPERATURE TRIP ON ELECTRIC HEAT

AHU POINTS LIST					
NAME	FACTS	TYPE	R/W	GRAPHIC	ALARM
ZoneTemp	°F	AI	R	G	N
ZoneTempSp	°F	AI	R/W	G	N
ZoneTempAlmDelay	Min	AV	R/W	P	N
ZoneTempAlm	ALARM/NORMAL	BV	R	G	Y
ZoneHum	%RH	AI	R	G	N
FreezeStat	ALARM/NORMAL	BI	R	G	Y
SupAirTemp	°F	AI	R	G	N
SupFanCmd	ON/OFF	BI	R	G	N
SupFan	START/STOP	BO	R/W	G	N
SupFanSpdCmd	%	AO	R/W	G	Y
OutAirPrpCmd	% OPEN	AO	R/W	G	N
RetAirDprCmd	% OPEN	AO	R/W	G	N
ExhAirDprCmd	% OPEN	AO	R/W	G	N
ChWtrLvCmd	% OPEN	AO	R/W	G	N
OccCmd	OCCUPIED/UNOCCUPIED	BV	R/W	G	Y
UnoccAHUClgCall	N/A	BV	R	G	N
SupFanRtTotal	Min	AV	R	P	N
SupFanRunFailDelay	Min	AV	R/W	P	N
SupFanRunFailAlm	ALARM/NORMAL	BV	R	G	Y
SupAirTempSp	°F	AV	R/W	G	Y
SupAirTempSpMax	°F	AV	R/W	P	N
SupAirTempSpMin	°F	AV	R/W	P	N
ClgLockOutSp	%	AV	R/W	G	Y
ClgLockOutSpDb	%	AV	R/W	P	N
ElecHtgEnableCmd	START/STOP	AO	R/W	G	Y
ElecHtgSts	AMPS	AI	R	G	N
ElecHtgLockout	N/A	AV	R/W	G	N
ElecHtgSafetyAlm	ALARM/NORMAL	AV	R	G	Y
OutAirPrMinPosSp	% OPEN	AV	R/W	G	N
MaxFlwOutAirDprPosSp	% OPEN	AV	R/W	P	N
MaxFlwFanSpdPct	%	AV	R/W	P	N
MinFlwOutAirDprPosSp	% OPEN	AV	R/W	P	N
MinFlwFanSpdPct	%	AV	R/W	P	N
LowSupAirTempAlmSp	°F	AV	R/W	G	N
LowSupAirTempAlmDelay	Sec	AV	R/W	P	N
LowSupAirTempAlm	ALARM/NORMAL	BV	R	G	Y
LowSupAirTempAlmReset	RESET/NORMAL	BV	R/W	G	N
OutAirFlowAlm	ALARM/NORMAL	BV	R	G	Y
OutAirFlowAlmDelay	Min	AV	R/W	P	N

NOTES:
 For the graphic column, any points with a G should be shown on the schematic graphic. All points with a P should be shown on a separate parameter page, with a link to the schematic graphic. Provide a link on the parameter page to a PDF of the sequence of operation and equipment schematic.
 *Provide all points available through the BACnet interface to a separate equipment parameter page with a link to the schematic graphic for each piece of integrated equipment. Up to 15 additional points shall be exposed on the schematic graphic at the request of the Engineer or Commissioning Agent. Any numeric status points shall be converted to their text value using a multistate variable.

FCU BAS KEYED NOTES	
1.	EXISTING SPACE TEMPERATURE SENSOR TO REMAIN.
2.	BASC TO FURNISH AND INSTALL CURRENT SENSOR TO MONITOR FAN STATUS.
3.	BASC TO FURNISH NEW CONTROL VALVE AND ACTUATOR. MC TO INSTALL NEW CONTROL VALVE. BASC RESPONSIBLE FOR FURNISHING, INSTALLING, AND WIRING THE ACTUATOR.
4.	EXISTING ELECTRIC HEATING COIL AND EXISTING POINTS TO REMAIN AND BE RE-USED.





2 FAN COIL UNIT - CONTROLS SCHEMATIC

SCALE: NO SCALE

FCU SEQUENCE OF OPERATION

1. SYSTEM ENABLE/DISABLE.
 - 1. THE FAN COIL SHALL BE ENABLED BY AN OCCUPANCY SCHEDULE.
 - 2. BAS TO COORDINATE WITH OWNER FOR OCCUPANCY SCHEDULE
2. DURING UNOCCUPIED MODES THE UNIT SHALL CONTROL TO A ZONE TEMPERATURE SETPOINT OF 72°F (ADJ.) WITH A ±2°F (ADJ) DEADBAND.
 - a. PROVIDE A 5 MIN (ADJ) DELAY WHEN SWITCHING FROM HEATING TO COOLING MODE.
 - b. ALLOW THE USER TO ADJUST THE SETPOINT ±2°F (ADJ) LOCALLY AT THE THERMOSTAT.
 - c. ALLOW THE USER TO MANUALLY OCCUPY THE UNIT FOR AT MOST 2 HRS (ADJ).
3. DURING UNOCCUPIED MODES THE UNIT SHALL MAINTAIN AN UNOCCUPIED COOLING SETPOINT OF 80°F (ADJ) AND AN UNOCCUPIED HEATING SETPOINT OF 65°F (ADJ).
 - a. THE UNIT SHALL STAY IN UNOCCUPIED COOLING MODE UNTIL THE SPACE TEMPERATURE IS BELOW 76°F (ADJ).
 - b. THE UNIT SHALL STAY IN UNOCCUPIED HEATING MODE UNTIL THE SPACE TEMPERATURE IS ABOVE 68°F (ADJ).
4. SUPPLY FAN CONTROL
 - 1. THE SUPPLY FAN SHALL RUN CONTINUOUSLY DURING OCCUPIED MODES.
 - 2. THE SUPPLY FAN SHALL CYCLE ON FOR UNOCCUPIED MODES.
 - 3. PROVIDE A TOTAL RUNTIME FOR THE SUPPLY FAN.
 - 4. IF THE SUPPLY FAN IS COMMANDED ON AND STATUS IS NOT PROVEN IN 2 MIN (ADJ) SEND A FAN RUN FAILURE ALARM TO THE OPERATOR WORKSTATION.
5. SUPPLY FAN SPEED CONTROL
 - 1. DURING NORMAL OPERATION THE FAN SHALL RUN AT A BALANCER DETERMINED SPEED.
 - 2. IF THE UNIT IS IN HEATING MODE AND THE HEATING PID IS AT 100% (ADJ) FOR 15 MINS (ADJ) INCREASE THE FAN SPEED TO 100% (ADJ).
 - 3. IF THE UNIT IS IN COOLING MODE AND THE COOLING PID IS AT 100% (ADJ) FOR 15 MINS (ADJ) INCREASE THE FAN SPEED TO 100% (ADJ).
6. TEMPERATURE CONTROL
 - 1. COOLING
 - a. WHEN THE UNIT IS IN COOLING MODE AND THE CHILLER SYSTEM IS ENABLED, THE CHILLED WATER VALVE SHALL MODULATE TO MAINTAIN THE DISCHARGE AIR TEMPERATURE SETPOINT.
 - b. WHEN THE UNIT IS IN HEATING MODE, THE CHILLED WATER VALVE SHALL CLOSE.
 - 2. HEATING
 - a. THE DUCT MOUNTED ELECTRIC HEATING COIL SHALL BE ENABLED WHEN THE OUTSIDE AIR TEMPERATURE IS BELOW 30°F (ADJ) WITH A ±5°F (ADJ) DEADBAND.
 - b. THE DUCT MOUNTED ELECTRIC HEATING COIL SHALL BE MODULATED TO MAINTAIN THE DISCHARGE AIR TEMPERATURE SETPOINT.
 - 3. DISCHARGE AIR TEMPERATURE SETPOINT CONTROL
 - 1. THE DISCHARGE AIR TEMPERATURE SETPOINT SHALL MODULATE TO MAINTAIN THE ZONE TEMPERATURE SETPOINT.
 - 2. WHEN THE ZONE IS SATISFIED THE DISCHARGE AIR TEMPERATURE SETPOINT SHALL BE EQUAL TO THE ZONE TEMPERATURE SETPOINT.
 - 3. WHEN THE UNIT IS IN HEATING MODE THE DISCHARGE AIR TEMPERATURE SETPOINT SHALL INCREASE FROM THE ZONE TEMPERATURE SETPOINT TO A MAXIMUM OF 95°F (ADJ) AS THE HEATING PID LOOP INCREASES FROM 0% (ADJ) TO 100% (ADJ).
 - 4. WHEN THE UNIT IS IN COOLING MODE THE DISCHARGE AIR TEMPERATURE SETPOINT SHALL DECREASE FROM THE ZONE TEMPERATURE SETPOINT TO A MINIMUM OF 55°F (ADJ) AS THE COOLING PID LOOP INCREASES FROM 0% (ADJ) TO 100% (ADJ).
7. ALARMS
 - 1. CRITICAL ALARMS SHALL BE ANNUNCIATED AT THE OPERATOR WORKSTATION AND EMAILED TO THE OWNER.
 - 2. CRITICAL ALARMS SHALL INCLUDE THE FOLLOWING:
 - a. SPACE TEMPERATURE IS BELOW 60°F (ADJ) FOR 5 MINS (ADJ) OR ABOVE 85°F (ADJ) FOR 5 MIN (ADJ).
 - b. SUPPLY FAN FAILURE

FCU POINTS LIST					
NAME	FACTS	TYPE	R/W	GRAPHIC	ALARM
ZoneTemp	°F	AI	R	G	Y
ZoneTempSp	°F	AI	R/W	G	N
ZoneTempAlmDelay	Min	AV	R/W	P	N
ZoneTempAlm	ALARM/NORMAL	BV	R	G	Y
SupAirTemp	°F	AI	R	G	N
SupFanCmd	ON/OFF	BI	R	G	N
SupFan	START/STOP	BO	R/W	G	Y
SupFanSpdCmd	%	AO	R/W	G	Y
ChWtrLvCmd	% OPEN	AO	R/W	G	Y
OccCmd	OCCUPIED/UNOCCUPIED	BV	R/W	G	Y
UnoccAHUClgCall	N/A	BV	R	G	N



HVAC EQUIPMENT WIRING SCHEDULE																																									
TAG	DESCRIPTION	VOLT	PHASE	LOAD				OCPD		FEED FROM		FEEDER/BRANCH WIRING				EQUIPMENT CONTROLLER						LOCAL DISCONNECT SWITCH						EQUIPMENT CONNECTION													
				HP	KW	FLA	MCA	SIZE	POLE	PANEL	CKT.	SETS	NO.	SIZE	GND.	CONDUIT	P.B	F.B	I.B	SIZE	TYPE	DISC. SW	OCPD	POLE	ENCL.	SEE NOTE	P.B	F.B	I.B	SIZE	TYPE	POLE	ENCL.	SEE NOTE	P.B	F.B	I.B	RECP.	CPC	HWC	FWC
AHU-5B-3	FAN COIL UNIT	480	3	-	7	11.1	13.2	15	3	EL-3-1	-	1	3	12	12	3/4"	M.C.	-	-	-	-	-	-	-	-	-	6	E.C.	-	-	-	-	YES	YES	4						
AHU-6-3B	FAN COIL UNIT	480	3	-	25	34	41.5	45	3	EL7-1	2,4,6	1	3	8	10	3/4"	M.C.	-	-	-	-	-	-	-	-	-	6	E.C.	-	-	-	-	YES	YES	4						
AHU-7D-1	FAN COIL UNIT	480	3	-	9.9	14.7	17.7	20	3	EL7-1	7,9,11	1	3	12	12	3/4"	M.C.	-	-	-	-	-	-	-	-	-	6	E.C.	-	-	-	-	YES	YES	4						
ESUH-1	UNIT HEATER	480	3	-	3	3.6	-	15	3	HDP1	-	1	3	12	12	3/4"	-	-	-	-	-	-	-	-	-	5	E.C.	-	-	-	-	YES	YES	4							
ESUH-2	UNIT HEATER	480	3	-	5	6	-	15	3	HP-6-5A	37,39,41	1	3	12	12	3/4"	-	-	-	-	-	-	-	-	-	5	E.C.	-	-	-	-	YES	YES	4							
ESUH-3	UNIT HEATER	480	3	-	5	6	-	15	3	HP-6-1B	37,39,41	1	3	12	12	3/4"	-	-	-	-	-	-	-	-	-	5	E.C.	-	-	-	-	YES	YES	4							
ESUH-4	UNIT HEATER	480	3	-	10	12	-	15	3	HDP1	-	1	3	12	12	3/4"	-	-	-	-	-	-	-	-	-	5	E.C.	-	-	-	-	YES	YES	4							
ESUH-5	UNIT HEATER	480	3	-	5	6	-	15	3	HP-1-5B	1,3,5	1	3	12	12	3/4"	-	-	-	-	-	-	-	-	-	5	E.C.	-	-	-	-	YES	YES	4							
ESUH-6	UNIT HEATER	480	3	-	10	12	-	15	3	HP-1-3A(1)	14,16,18	1	3	12	12	3/4"	-	-	-	-	-	-	-	-	-	5	E.C.	-	-	-	-	YES	YES	4							
ESUH-7	UNIT HEATER	480	3	-	10	12	-	15	3	HP-1-3A(1)	26,28,30	1	3	12	12	3/4"	-	-	-	-	-	-	-	-	-	5	E.C.	-	-	-	-	YES	YES	4							
ESUH-8	UNIT HEATER	480	3	-	5	6	-	15	3	HDP-1-1	-	1	3	12	12	3/4"	-	-	-	-	-	-	-	-	-	5	E.C.	-	-	-	-	YES	YES	4							
FCU-1	FAN COIL UNIT	120	1	-	-	6.6	-	15	1	RP-5-1B	-	1	2	12	12	3/4"	-	-	-	-	-	-	-	-	-	6	E.C.	-	-	-	-	YES	YES	-							
FCU-2	FAN COIL UNIT	120	1	-	-	6.6	-	15	1	RP-5-1B	-	1	2	12	12	3/4"	-	-	-	-	-	-	-	-	-	6	E.C.	-	-	-	-	YES	YES	-							
GENERAL NOTES:												PB: PROVIDED BY (FURNISH AND INSTALL)						NOTE #1						E.C. SHALL PROVIDE MOUNTING/RACKING FOR STARTER TYPES (F/NR, F/R, PRMS, 2SP1W, & 2SP2W)																	
1 E.C. SHALL REVIEW THE ARCHITECTURAL, MECHANICAL, PLUMBING, AND FIRE PROTECTION CONTRACT DOCUMENTS, AND SHOP DRAWINGS FOR FINAL EQUIPMENT LOCATION, ELEVATION, AND POWER REQUIREMENTS PRIOR TO INSTALLING CONDUITS.												FB: FURNISHED BY						NOTE #1						E.C. SHALL PROVIDE THERMAL OVERLOADS FOR STARTERS PER OEM/FIELD VERIFICATION																	
2 E.C. SHALL REVIEW THE LOAD REQUIREMENTS WITH THE OEM PRIOR TO INSTALLING CONDUIT.												IB: INSTALLED BY						E.C. SHALL PROVIDE TWO SETS OF FORM "C" AUX CONTACTS FOR ALL STARTER TYPES												E.C. SHALL PROVIDE 120Vac CONTROL COIL FOR STARTERS TYPES (F/NR, F/R, 2SP1W, & 2SP2W)											
3 E.C. SHALL VERIFY IN THE FIELD THE OCPD REQUIREMENTS WITH THE OEM PRIOR TO INSTALLING CONDUIT. OCPD RATINGS ARE DERIVED FROM THE OEM'S SPECIFICATIONS.												ENCL.: NEMA ENCLOSURE						NOTE #2						E.C. SHALL PROVIDE 24Vac CONTROL COIL FOR POWER RELAYS/MANUAL STARTER "PPRMS"																	
4 E.C. SHALL VERIFY IN THE FIELD THE CONTACTOR/STARTER/VFD/PRMS/OEM CONTROLLER/DISCONNECT RATINGS WITH THE OEM PRIOR TO INSTALLING CONDUIT.												HWC: HARD WIRE CONNECTION						NOTE #2						E.C. SHALL PROVIDE MOUNTING/RACKING FOR VARIABLE FREQUENCY CONTROLLER "VFD"																	
5 E.C. SHALL VERIFY IN THE FIELD THE THERMAL OVERLOAD RATINGS WITH THE OEM. PROVIDE OVERLOADS PER OEM RECOMMENDATIONS.												FWC: FLEXIBLE WHIP CONDUIT						NOTE #3						E.C. SHALL CALIBRATE SOLID STATE OVERLOADS PER OEM/FIELD VERIFICATION RESULTS																	
6 E.C. SHALL VERIFY IN THE FIELD WITH THE OEM PRIOR TO INSTALLING CONDUIT. E.C. SHALL LOCATE THE DISCONNECT SWITCH WITHIN 5FT AND WITHIN SIGHT OF THE EQUIPMENT.												CPC: CORD AND PLUG CONNECTION						NOTE #3						E.C. SHALL PROVIDE FOUR SETS OF FORM "C" AUX CONTACTS WITHIN THE VFD ENCLOSURE																	
7 E.C. SHALL PROVIDE CONNECTIONS TO MOTOR/LISTED EQUIPMENT. PROVIDE A Cu EQUIPMENT GROUND (EGC) FROM THE DISCONNECT SWITCH TO THE MOTOR/LISTED EQUIPMENT CONNECTION POINT/JUNCTION BOX.												FVN: FULL VOLTAGE NON-REVERSING MAGNETIC STARTER						NOTE #4						E.C. SHALL PROVIDE MOUNTING/RACKING FOR DISCONNECT SWITCHES																	

ELECTRICAL ABBREVIATIONS

A,AMP	AMPERE	KEC	KITCHEN EQUIPMENT CONTRACTOR
ABV	ABOVE	KO	KNOCKOUT
AC	ALTERNATING CURRENT	KS	KEYED SWITCH
ACL	ACROSS THE LINE	KVA	KILOVOLT-AMPERE
ACT	ACOUSTICAL CEILING TILE	KW	KILOWATT
AD	ACCESS DOOR	KWH	KILOWATT-HOUR
ADA	AMERICANS WITH DISABILITIES ACT	L#	LINE
ADJ	ADJUSTABLE	LCD	LIQUID CRYSTAL DISPLAY
AFF	ABOVE FINISHED FLOOR	LED	LIGHT EMITTING DIODE
AFCI	ARC FAULT CIRCUIT INTERRUPTER	LS	LOUD SPEAKER
AF	AMP FUSE	LTG	LIGHTING
AHJ	AUTHORITY HAVING JURISDICTION	LV	LOW VOLTAGE
AIC	AMPERES INTERRUPTING CAPACITY	MAG	MAGNETIC
AIEE	AMERICAN INSTITUTE OF ELECTRICAL ENGINEERS	MAN	MANUAL
AL	ALUMINUM	MAT	MATERIAL
ALM	ALARM	MAX	MAXIMUM
ALT	ALTERNATE	MC	MECHANICAL CONTRACTOR
ANN	ANNUNCIATOR	MCA	MINIMUM CIRCUIT AMPS
AS	AMP SWITCH	MCB	MAIN CIRCUIT BREAKER
AT	AMP TRIP	MCC	MOTOR CONTROL CENTER
ATS	AUTOMATIC TRANSFER SWITCH	MCCB	MOLDED CASE CIRCUIT BREAKER
AUTO	AUTOMATIC	MCM	THOUSAND CIRCULAR MILS
AVC	ABOVE COUNTER	MCS	MOLDED CASE SWITCH
AWG	AMERICAN WIRE GAUGE	MECH	MECHANICAL
BAL	BALLAST	MFR	MANUFACTURER
BASC	BUILDING AUTOMATION SYSTEM CONTRACTOR	MH	METAL HALIDE
BGB	BUILDING GROUND BOX	MICRO	MICROWAVE
BHP	BREAK HORSEPOWER	MIN	MINIMUM
BKR	BREAKER	MISC	MISCELLANEOUS
C	CONDUIT	MOCP	MAXIMUM OVER CURRENT PROTECTION
CAB	CABINET	MTD	MOUNTED
CAT	CATALOG	MTR	MOTOR
CATV	CABLE TELEVISION	MTS	MANUAL TRANSFER SWITCH
C.B.	CIRCUIT BREAKER	MV	MERCURY VAPOR
CBC	CHICAGO BUILDING CODE	N,NEUT	NEUTRAL
CCTV	CLOSED CIRCUIT TELEVISION	NAC	NOTIFICATION APPLIANCE CIRCUITS
CCW	COUNTERCLOCKWISE	NC	NORMALLY CLOSED
CD	CANDELA	NEC	NATIONAL ELECTRICAL CODE
CECO	COMMONWEALTH EDISON COMPANY	NEMA	NATIONAL ELECTRICAL MANUFACTURERS' ASSOCIATION
CIC	CABLE IN CONDUIT	NIC	NOT IN CONTRACT
CKT	CIRCUIT	NL	NIGHT LIGHT
CL	CENTER LINE	NO	NORMALLY OPENED
CLG	CEILING	NTS	NOT TO SCALE
CLK	CLOCK	OCP	OVER CURRENT PROTECTION
CLO	CLOSET	OL	OVERLOAD
CLSD	CLOSED	OVHD	OVERHEAD
COAX	COAXIAL	P	POLES
COL	COLUMN	PA	PUBLIC ADDRESS
COM	COMMON	PB	PULL BOX
COMED	COMED COMPANY	PE	PROFESSIONAL ENGINEER
CONC	CONCRETE	PCU	PACKAGED CONTROL UNIT
CT	CURRENT TRANSFORMER	PH	PHASE
CU	COPPER	PL	PROPERTY LINE
C.U.	COEFFICIENT OF UTILIZATION	PNL	PANEL
CUH	CABINET UNIT HEATER	PRI	PRIMARY
CW	CLOCKWISE	PROT.	PROTECTION OR PROTECTIVE
DB	DECIBEL	PT	POTENTIAL TRANSFORMER
DC	DIRECT CURRENT	PTD	PAINTED
DEG	DEGREE	PVC	POLYVINYL CHLORIDE (ELECTRIC GRADE)
DEMO	DEMOLITION	PWR	POWER
DN	DOWN	QTY	QUANTITY
DO	DRAW OUT	R	DISCONNECT AND REMOVE
DPDT	DOUBLE POLE DOUBLE THROW	RC	REMOTE CONTROL
DPST	DOUBLE POLE SINGLE THROW	RCP	REFLECTED CEILING PLAN
DS	DISCONNECT SWITCH	REF	REFRIGERATOR
DT	DUST TIGHT	REV	REVERSE OR REVISION
DW	DISHWASHER	RECP	RECEPTACLE
DWG	DRAWING	RM	ROOM
EA	EACH	RMC	RIGID METAL CONDUIT (GALVANIZED)
EC	ELECTRICAL CONTRACTOR	RMS	ROOT MEAN SQUARE
EF	EXHAUST FAN	RT	RAIN TIGHT
EHD	ELECTRIC HAND DRYER	RTG	RATING
ELEC	ELECTRIC	RVNR	REDUCED VOLTAGE NON-REVERSING
ELEV	ELEVATOR	RVR	REDUCED VOLTAGE REVERSING
EM	EMERGENCY	S	SWITCH
EMT	ELECTRIC METALLIC TUBING (THIN WALL CONDUIT)	SEC	SECONDARY
ENG	ENGINEER	SC	SHORT CIRCUIT
EP	EXPLOSION PROOF	SCH	SCHEDULE
EPO	ELECTRIC POWER OFF	SF	SQUARE FOOT
EQ	EQUIPMENT	SP	SINGLE POLE
ER#	EXISTING TO RELOCATE	SPC	SINGLE POINT CONNECTION
EUH	ELECTRIC UNIT HEATER	SPDT	SINGLE POLE DOUBLE THROW
EWC	ELECTRIC WATER COOLER	SPEC	SPECIFICATION
EWH	ELECTRIC WALL HEATER	SPKR	SPEAKER
EX	EXISTING TO REMAIN	SPST	SINGLE POLE SINGLE THROW
EXT	EXTERIOR	SS	STAINLESS STEEL
F	FUSE	STA	STATION
FA	FIRE ALARM	STD	STANDARD
FB	FLOOR BOX	SW	SWITCH
FC	FOOTCANDLE	SWBD	SWITCHBOARD
FDC	FIRE DEPARTMENT CONNECTION	SWGR	SWITCHGEAR
FDR	FEEDER	SYM	SYMMETRICAL
FF	FINISHED FLOOR	SYS	SYSTEM
FIXT	LIGHT FIXTURE	T	TRIP
FLA	FULL LOAD AMPS	TC	TERMINAL CABINET
FLUOR	FLUORESCENT	TEL	TELEPHONE
FPB	FAN POWERED BOX	TEL.CL	TELEPHONE CLOSET
FS	FUSED SWITCH	TEMP	TEMPORARY
FT	FEET	TERM.	TERMINAL
FURN	FURNITURE	TL	TWIST LOCK
FVNR	FULL VOLTAGE NON-REVERSING	TRF	TRANSFORMER
FVR	FULL VOLTAGE REVERSING	TS	TIME SWITCH
FWD	FORWARD	TTC	TELEPHONE TERMINAL CABINET
G,GRD	GROUND	TV	TELEVISION
GALV	GALVANIZED	TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSION
GC	GENERAL CONTRACTOR	TX	TRANSFORMER
GEN	GENERATOR	TYP	TYPICAL
GFCI	GROUND FAULT CIRCUIT INTERRUPTER	UG	UNDERGROUND
GHW	GALVANIZED HEAVY WALL STEEL CONDUIT	UH	UNIT HEATER
H	HOT	UL	UNDERWRITER'S LABORATORIES
HD	HEAVY DUTY	UNG	UNGROUNDED
HDCP	HANDICAPPED	UNC	UNLESS NOTED OTHERWISE
HGB	HOGAN GROUND BOX	UPS	UNINTERRUPTIBLE POWER SUPPLY
HID	HIGH INTENSITY DISCHARGE	V	VOLT
HOA	HANDS-OFF-AUTO	VA	VOLT-AMPERE
HP	HORSEPOWER	VFD	VARIABLE FREQUENCY DRIVE
HPS	HIGH PRESSURE SODIUM	VIF	VERIFY IN FIELD
HTR	HEATER	VP	VAPOR PROOF
HV	HIGH VOLTAGE	VT	VAPOR TIGHT
HZ	HERTZ (CYCLES/SECOND)	W	WATT OR WIRE (DEPENDING ON CONTEXT)
I	CURRENT	W/D	WASHER DRYER
IC	INTERRUPTING CAPACITY	WG	WIRE GUARD
IG	ISOLATED GROUND	W/O	WITHOUT
IMC	INTERMEDIATE GRADE CONDUIT	WP	WEATHERPROOF
IN	INCH	WT	WATER TIGHT
INC	INCANDESCENT	X	DEMOLISH EXISTING
INFO	INFORMATION	XS	REMOVE AND SALVAGE
INSUL	INSULATION	YR	YEAR
ISC	INSTANTANEOUS SHORT CIRCUIT		
JB	JUNCTION BOX		

NOTE: NOT ALL ABBREVIATIONS LISTED ABOVE MAY BE USED OR APPEAR IN THESE DRAWINGS.

PROJECT:
RATE FIELD - HVAC FY2026

333 WEST 35TH STREET
CHICAGO, ILLINOIS 60616

DRAWING TITLE:

DESIGNED BY:	LF
CHECKED BY:	BT
PROJECT NO.:	25080
SCALE:	NO SCALE
SHEET NO.:	1

E0.01



ISSUE/REVISION:
REV DATE DESCRIPTION
1/30/2026 ISSUED FOR BID


PROJECT:
RATE FIELD - HVAC FY2026

333 WEST 35TH STREET
CHICAGO, IL 60616

DRAWING TITLE:
ELECTRICAL PLAN - SERVICE
LEVEL

DESIGNED BY: LF
CHECKED BY: BT
PROJECT NO: 25080
SCALE: 1/32" = 1'-0"
SHEET NO.

E1.01





ISSUE/REVISION:
REV DATE DESCRIPTION
1/30/2026 ISSUED FOR BID



PROJECT:
RATE FIELD - HVAC FY2026

333 WEST 35TH STREET
CHICAGO, IL 60616

DRAWING TITLE:
ELECTRICAL PLAN - 200 LEVEL

DESIGNED BY: LF
CHECKED BY: BT
PROJECT NO: 25080
SCALE: 1/32" = 1'-0"
SHEET NO.

E1.02





araeng.com | (708) 236-0300



CLINICS AUTHORITY




JECT:
E FIELD - HVAC FY2026

WEST 35TH STREET
AGO, IL 60616

GNED BY:	LF
CKED BY:	BT
JECT NO:	25080
E:	1/32" = 1'-0"
ET NO.	

E1.03





araeng.com | (708) 236-0300

araeng.com | (708) 236-0300




PROJECT: THE FIELD - HVAC FY2026

WEST 35TH STREET
AGO, IL 60616

GNED BY:	LF
CKED BY:	BT
JECT NO:	25080
E:	1/32" = 1'-0"
ET NO.	

E1.04







ISSUE/REVISION:	REV	DATE	DESCRIPTION
			1/30/2026 ISSUED FOR BID
PROJECT:			RATE FIELD - HVAC FY2026
333 WEST 35TH STREET			CHICAGO, IL 60616
DRAWING TITLE:			ELECTRICAL PLANS
DESIGNED BY:	LF		
CHECKED BY:	BT		
PROJECT NO.:	25080		
SCALE:	As indicated		
SHEET NO.			

KEYED NOTES


- EXISTING DISTRIBUTION PANELBOARD TO REMAIN. FURNISH AND INSTALL (3) NEW 15A FUSES WITHIN THE EXISTING SPARE 30A/3P FUSE SWITCH. NEW FUSES SHALL HAVE THE SAME MAKE, MODEL, AND AIC RATING AS THE EXISTING FUSES WITHIN THE PANELBOARD. TERMINATE NEW BRANCH CIRCUIT CONDUIT AND WIRES TO EXISTING SPARE 30A/3P FUSE SWITCH.
- MECHANICAL CONTRACTOR SHALL FURNISH AND ELECTRICAL CONTRACTOR SHALL INSTALL NEW DISCONNECT SWITCH FOR NEW UNIT HEATER. REFER TO HVAC EQUIPMENT SCHEDULE FOR SPECIFIC REQUIREMENTS AND CHARACTERISTICS OF NEW EQUIPMENT.
- EXISTING PANELBOARD TO REMAIN. FURNISH AND INSTALL (3) NEW 100A FUSES WITHIN THE EXISTING 100A/3P SPARE FUSE SWITCH. NEW FUSES SHALL HAVE THE SAME MAKE, MODEL, AND AIC RATING AS THE EXISTING FUSES WITHIN THE PANELBOARD. TERMINATE NEW FEEDER WIRES TO EXISTING SPARE 100A/3P FUSE SWITCH FOR THE NEW PANELBOARD TO BE INSTALLED.
- EXISTING PANELBOARD TO REMAIN. REPLACE EXISTING SPARE 20A/3P CIRCUIT BREAKERS IN SPACES #14, #16, #18, AND #26, #28, #30 WITH NEW 15A/3P CIRCUIT BREAKERS. NEW CIRCUIT BREAKER SHALL HAVE THE SAME MAKE, MODEL, AND AIC RATING AS THE EXISTING CIRCUIT BREAKERS WITHIN THE PANELBOARD. TERMINATE (2) NEW BRANCH CIRCUIT CONDUIT AND WIRES TO THE SAME LOCATION AS THE REPLACED CIRCUIT BREAKERS.
- FURNISH AND INSTALL NEW BRANCH CIRCUIT CONDUIT AND WIRES FROM EXISTING DISTRIBUTION PANELBOARD TO NEW PANELBOARD. REFER TO ELECTRICAL SINGLE LINE DIAGRAM FOR SPECIFIC CONDUIT AND WIRE SIZES.




① ELECTRICAL PLAN - ELECTRICAL ROOM 1.17.3 - GROUND LEVEL




③ ELECTRICAL PLAN - ELECTRICAL ROOM 3.17.05 - 200 LEVEL



④ ELECTRICAL PLAN - ELECTRICAL ROOM 6.29.1 - 500 LEVEL



② ELECTRICAL PLAN - ELECTRICAL ROOM 1.29.07 - GROUND LEVEL



KEYED NOTES

- 1 EXISTING PANELBOARD TO REMAIN. REPLACE EXISTING (3) SPARE 20A/1P CIRCUIT BREAKERS IN SPACES #1,3,5 WITH A NEW 15A/3P CIRCUIT BREAKER. NEW CIRCUIT BREAKER SHALL HAVE THE SAME MAKE, MODEL, AND AIC RATING AS THE EXISTING CIRCUIT BREAKERS WITHIN THE PANELBOARD. TERMINATE NEW BRANCH CIRCUIT CONDUIT AND WIRES TO SAME LOCATION AS THE REPLACED CIRCUIT BREAKER.
- 2 MECHANICAL CONTRACTOR SHALL FURNISH AND ELECTRICAL CONTRACTOR SHALL INSTALL NEW DISCONNECT SWITCH FOR NEW UNIT HEATER. REFER TO HVAC EQUIPMENT SCHEDULE FOR SPECIFIC REQUIREMENTS AND CHARACTERISTICS OF NEW EQUIPMENT.
- 3 EXISTING DISTRIBUTION PANELBOARD TO REMAIN. TERMINATE (2) NEW BRANCH CIRCUIT CONDUIT AND WIRES TO THE (2) EXISTING 15A/3P CIRCUIT BREAKERS.

ELARA
elaraeng.com | (708) 236-0300

ISFA
ILLINOIS SPORTS
FACILITIES AUTHORITY



ISSUE/REVISION:		
REV	DATE	DESCRIPTION
	1/30/2026	ISSUED FOR BID

PROJECT:
RATE FIELD - HVAC FY2026

333 WEST 35TH STREET
CHICAGO, IL 60616

DRAWING TITLE:
ELECTRICAL PLANS


DESIGNED BY: LF
CHECKED BY: BT
PROJECT NO: 25080
SCALE: As indicated
SHEET NO.

E2.03


1 ELECTRICAL PLAN - ELECTRICAL ROOM 1.44.02 - GROUND LEVEL



2 ELECTRICAL PLAN - ELEV. 12 & 13 MACHINE ROOM - GROUND LEVEL







<p>010000. GENERAL CONDITIONS AND REQUIREMENTS</p> <p>A. GENERAL</p> <ol style="list-style-type: none"> ALL ELECTRICAL WORK INCLUDING BUT NOT LIMITED TO INSTALLATION, GROUNDING, EQUIPMENT, AND DEVICES SHALL CONFORM TO THE REQUIREMENTS OF ALL AUTHORITIES HAVING JURISDICTION AND APPLICABLE NATIONAL, STATE, CITY, AND MUNICIPAL BUILDING CODES. ALL ELECTRICAL WORK SHALL CONFORM TO NATIONAL AND LOCAL STANDARDS AND GUIDELINES INCLUDING BUT NOT LIMITED TO THE LATEST VERSIONS OF THE FOLLOWING: <ul style="list-style-type: none"> a. ANSI - AMERICAN NATIONAL STANDARDS INSTITUTE b. ILLUMINATING ENGINEERING SOCIETY OF NORTH AMERICA (IES) c. NATIONAL ELECTRICAL SAFETY CODE (NESC) d. NFPA - NATIONAL FIRE PROTECTION ASSOCIATION: STANDARD FOR ELECTRICAL SAFETY IN THE WORKPLACE (NFPA 70E) e. UNDERWRITERS LABORATORY (OR OTHER RECOGNIZED INSPECTING AGENCY) f. THE NATIONAL ELECTRICAL CODE (NEC) g. ENERGY CODE (IECC) ALL MATERIALS SHALL BE LISTED BY AN APPROVED LABORATORY AND SHALL BE NEW AND THE BEST OF THEIR RESPECTIVE KINDS AND SHALL BE INSTALLED AND APPLIED AS INTENDED AND REQUIRED BY THE MANUFACTURER. ELECTRICAL WORK SHALL INCLUDE, BUT NOT BE LIMITED TO: <ul style="list-style-type: none"> a. ALL MATERIALS b. EQUIPMENT, TOOLS, AND LABOR REQUIRED FOR A COMPLETE AND CODE COMPLIANT SYSTEM. c. ANY OSHA REQUIREMENTS THAT MAY APPLY TO THE WORK UNDER THIS CONTRACT INCLUDING BUT NOT LIMITED TO SAFETY MEETINGS, STRICT LOCKOUT/TAGOUT PROCEDURES, AND PROPER PROTECTIVE EQUIPMENT. d. LABOR AND SPECIALTY MODELING SOFTWARE REQUIRED FOR INTERDISCIPLINARY COORDINATION AND FAMILIARIZATION WITH SITE CONDITIONS. e. TRAINING AND GATHERING OF DOCUMENTATION FOR CLOSEOUT PROCEDURES. THE DRAWINGS AND SPECIFICATIONS SHALL BE UNDERSTOOD TO COVER COMPLETE SYSTEMS ACCORDING TO THEIR INTENT AND MEANING AS DESCRIBED HEREIN. THIS SPECIFICATION IS INCLUSIVE FOR EACH ITEM, REQUIRING ALL LABOR, MATERIAL AND EQUIPMENT NECESSARY TO PROPERLY INSTALL, ALTER, ADJUST AND PUT IN OPERATION THE COMPLETE ELECTRICAL SYSTEM. THIS CONTRACTOR IS RESPONSIBLE FOR FURNISHING AND INSTALLING ALL ELECTRICAL COMPONENTS AND SYSTEMS AS REQUIRED FOR A FULLY FUNCTIONAL SYSTEM AND AS DESCRIBED HEREIN. ALL EQUIPMENT AND DEVICES SPECIFIED AND ADDITIONALLY REQUIRED WILL BE THE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR. IT WILL BE THE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR TO PURCHASE ALL EQUIPMENT AND FURNISH LABOR AND EQUIPMENT FOR A COMPLETE CODE COMPLIANT OPERATING ELECTRICAL SYSTEM. THE CONTRACTOR IS RESPONSIBLE FOR THE PROPER LAYOUT AND CONSTRUCTION OF THE WORK INCLUDED IN THIS CONTRACT, INSTALLED ACCORDING TO THE APPLICABLE BUILDING CODES. SPECIFIC VOLTAGE AND CURRENT REQUIREMENTS ON THE ELECTRICAL DRAWINGS SHALL NOT RELIEVE THIS CONTRACTOR OF THE RESPONSIBILITY TO VERIFY THE VOLTAGE PRIOR TO PURCHASING OR ROUGH-IN WORK. THIS CONTRACTOR SHALL REVIEW ALL DEVICES AND EQUIPMENT FURNISHED BY HIS/HER CONTRACT AND THOSE FURNISHED BY OTHER CONTRACTORS IN AGREEMENT WITH THE DATA SHOWN ON THE DRAWINGS. THE E.C. SHALL PROVIDE FEEDERS, CABLES AND DEVICES THAT ARE IN ACCORDANCE WITH CODE. ITEMS, ACCESSORIES, AND DEVICES REASONABLY INFERABLE AS NECESSARY FOR THE COMPLETE AND PROPER OPERATION OF ANY SYSTEM SHALL BE PROVIDED BY THE CONTRACTOR FOR SUCH SYSTEM(S), WHETHER THEY ARE SPECIFICALLY CALLED FOR BY THE DRAWINGS AND/OR SPECIFICATIONS OR NOT. THE DRAWINGS MAY NOT SHOW COMPLETE OR ACCURATE DETAILS OF THE EXISTING FACILITY IN EVERY RESPECT. EXACT LOCATIONS AND RELATIONS ARE TO BE DETERMINED IN THE FIELD AND SHALL BE TO THE SATISFACTION OF THE OWNER. THIS CONTRACTOR SHALL VERIFY AND BE RESPONSIBLE FOR ALL FIELD MEASUREMENTS AND EXACT EQUIPMENT LOCATIONS. DRAWINGS ARE GENERALLY DIAGRAMMATIC. ROUTING OF CONDUIT AND RACEWAYS ARE SHOWN FOR CONCEPT, BUT DO NOT INTEND TO SHOW EVERY RISE, DROP, OFFSET, FITTING, NOR EVERY STRUCTURAL ELEMENT THAT MAY BE ENCOUNTERED DURING THE INSTALLATION OF THIS WORK. CONTRACTOR SHALL MAKE ANY REQUIRED CHANGES FROM THE GENERAL ROUTING SHOWN ON THESE DRAWINGS, SUCH AS OFFSETS, BENDS OR CHANGES IN ELEVATION DUE TO COORDINATION WITH THE WORK OF OTHER TRADES AND BUILDING CONSTRUCTION. ALL CHANGES SHALL BE MADE WITHOUT ADDITIONAL COST TO THE OWNER OR DELAY IN COMPLETION DATE OF THE PROJECT. IT IS INTENDED THAT EQUIPMENT SHALL BE LOCATED SYMMETRICALLY WITH THE ARCHITECTURAL ELEMENTS OF THE BUILDING. NOTWITHSTANDING THE FACT THAT LOCATIONS INDICATED BY THESE DRAWINGS MAY BE DISTORTED FOR CLEARNESS OF PRESENTATION, ENGINEER HAS RIGHT TO MOVE ANY EQUIPMENT OR DEVICE BY 10 FEET WITHOUT ANY ADDITIONAL COST TO OWNER. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO SUBMIT SHOP DRAWINGS FOR APPROVAL PRIOR TO ROUGH-IN. CONTRACTOR SHALL BE RESPONSIBLE AND PAY FOR ALL X-RAY IMAGING, CORING, CUTTING, PATCHING, REPAIRING AND REFINISHING OF BUILDING CONSTRUCTION REQUIRED TO ACCOMMODATE THE INSTALLATION OF THEIR WORK. ALL PATCHING, REPAIRING AND REFINISHING WORK SHALL BE PERFORMED BY THOSE REGULARLY INVOLVED IN THAT TRADE AND SHALL MATCH THE NEW CONSTRUCTION AS CLOSELY AS POSSIBLE. CARE SHALL BE TAKEN SO AS NOT TO DAMAGE THE EXISTING BUILDING CONSTRUCTION OR ITEMS THAT ARE TO REMAIN. ANY EXISTING FINISHES THAT ARE DAMAGED DURING THE INSTALLATION OF NEW WORK SHALL BE REPAVED, REPLACED AND PAID FOR BY THE INSTALLING CONTRACTOR. TO THE SATISFACTION OF THE ENGINEER AND OWNER. THIS CONTRACTOR IS RESPONSIBLE FOR SCHEDULING DELIVERY, RECEIVING, UNLOADING, UNCRATING, STORING, SETTING UP, PLACING, AND PROTECTING FROM DAMAGE AND THEFT OR WHETHER THE EQUIPMENT IS FURNISHED BY THE CONTRACTOR FOR THE ENTIRETY OF CONSTRUCTION. THIS REQUIREMENT ALSO APPLIES TO ITEMS FURNISHED BY THE OWNER TO THE ELECTRICAL CONTRACTOR. THIS CONTRACTOR SHALL COORDINATE THE DELIVERY TO MEET THE PROJECT COMPLETION DATES AS ESTABLISHED BY THE OWNER. REFER TO ARCHITECTURAL DRAWINGS FOR EXISTING BUILDING CONSTRUCTION THAT IS TO REMAIN AND, THEREFORE, SUBJECT TO PATCHING, REPAIRING, AND REFINISHING. ANY ITEMS AND EQUIPMENT SCHEDULED TO BE REMOVED SHALL BE THE OWNER'S RESPONSIBILITY. THE OWNER SHALL REMOVE CAREFULLY (SO AS NOT TO DAMAGE THEM) AND TURNED OVER TO THE OWNER. ALL OTHER ITEMS TO BE REMOVED SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND REMOVED FROM THE SITE. CONTRACTOR SHALL BE RESPONSIBLE FOR THEIR OWN CLEANUP DURING CONSTRUCTION. IF CONTRACTOR FAILS TO PROVIDE SUCH CLEANUP, THE ENGINEER WILL DIRECT ANOTHER CONTRACTOR TO PERFORM THE CLEAN-UP AND THE NEGLECTFUL CONTRACTOR SHALL PAY THE ASSOCIATED BACK-CHARGES AS DEEMED APPROPRIATE BY THE ENGINEER. ACCESS TO WORK AREAS, INCLUDING WORK SCHEDULED THEREIN, MUST HAVE PRIOR APPROVAL OF THE OWNER. ALL WORK AREAS WILL BE KEPT CLEAN BY THIS CONTRACTOR WITH THOROUGH CLEAN UP AT ENDS OF EACH DAY'S WORK. ALL EXISTING ELECTRIC SERVICE EQUIPMENT IS TO REMAIN OPERATIONAL DURING THE CONSTRUCTION PERIOD. ANY TEMPORARY WIRING OR REROUTING OF CIRCUITY TO ACHIEVE THIS IS BY THE ELECTRICAL CONTRACTOR. CONTRACTOR SHALL FURNISH MATERIALS AND USE INSTALLATION METHODS SUITABLE FOR THE ENVIRONMENTAL CONDITIONS OF THE AREA IN WHICH EQUIPMENT, FIXTURES AND DEVICES ARE INSTALLED. CONTRACTOR SHALL PROVIDE SLEEVES IN BEAMS, FLOORS, COLUMNS AND WALLS, AS REQUIRED BY JOB SITE CONDITIONS, AND/OR AS SPECIFIED, WHEN INSTALLING THEIR WORK. ALL BEAMS AND COLUMNS WHICH ARE REQUIRED TO BE SLEEVED SHALL BE CUT AND REINFORCED AS REQUIRED BY FIELD CONDITIONS AND LOCATIONS AND SIZES SHALL BE CHECKED AND APPROVED BY ENGINEER BEFORE CONTRACTOR CUTS ANY BUILDING STRUCTURAL MEMBER. CONTRACTOR SHALL REFER TO THE ARCHITECTURAL AND STRUCTURAL CONTRACT DRAWINGS (BEFORE SUBMITTING THEIR BIDS) TO FAMILIARIZE THEMSELVES WITH THE EXTENT OF THE GENERAL CONTRACTOR'S WORK, CEILING HEIGHTS AND CLEARANCE FOR INSTALLING THEIR WORK. CONTRACTOR SHALL STORE ALL MATERIALS AND EQUIPMENT SHIPPED TO THE SITE IN A PROTECTED AREA. IF MATERIAL IS STORED OUTSIDE OF THE BUILDING, IT MUST BE STORED OFF THE GROUND A MINIMUM OF SIX INCHES (6") ON 6' x 6' PLANKS AND/OR WOOD PALLETS. ALL PIPING AND DUCTWORK WILL HAVE THE ENDS CLOSED TO KEEP OUT DIRT AND OTHER DEBRIS. NO EQUIPMENT SHALL BE STORED ON THE SITE UNLESS IT IS SITTING ON WOOD PLANKS AND COMPLETELY PROTECTED WITH WEATHERPROOF COVERS. ALL MATERIALS AND EQUIPMENT MUST BE COMPLETELY COVERED WITH WATERPROOF TARPS OR VISQIN. ELECTRICAL CONTRACTOR SHALL COORDINATE ALL NON-ACCESSIBLE SYSTEM DEVICES, PULL BOXES AND EQUIPMENT, ETC. TO ACCESSIBLE CEILING AREAS. E.C. SHALL INCLUDE ALL COMPLETE COSTS FOR RELOCATION AND VERIFY SUCH CONDITIONS WITH ARCHITECTURAL CEILING PLANS PRIOR TO FINAL BID. ELECTRICAL CONTRACTOR SHALL FOLLOW NEMA NO. PB-1.1 1979 PUBLICATION, PART V PROCEDURES PRIOR TO EROGIZATION OF ANY SWITCHGEAR. THE ELECTRICAL CONTRACTOR SHALL USE ONLY TRAINED AND AUTHORIZED PROFESSIONAL ELECTRICAL CRAFT PERSONS. THE E.C. SHALL FURNISH ANY PERSONNEL SAFETY EQUIPMENT, LADDERS, MAN-LIFTS, AND POWERED HAND TOOLS THAT MAY BE REQUIRED. ALL POWERED TOOLS SHALL BE IN GOOD CONDITION WITH ALL GROUND CONDUCTOR IN PROPER OPERATION. VERIFY CODE CLEARANCES FOR ALL NEW ELECTRICAL WORK BEFORE PROCEEDING WITH CONSTRUCTION. PROVIDE ADEQUATE WORKING CLEARANCES, DEDICATED EQUIPMENT SPACE, AND LEAK PROTECTION SYSTEMS AS REQUIRED BY APPLICABLE ELECTRICAL CODES. COORDINATE USAGE OF AVAILABLE SPACE WITH ALL TRADES. IN THE EVENT OF CONFLICTS, NOTIFY THE ENGINEER BEFORE PROCEEDING WITH THE WORK. B. CONFLICT IN DOCUMENTS 		<p>1. GENERALLY, THE DRAWINGS ESTABLISH THE LOCATION, QUANTITY AND RELATIONSHIP OF THE PARTS OF THE WORK. AND THE SPECIFICATIONS DEFINE THE TYPE AND QUALITY OF MATERIALS AND WORKMANSHIP. WORK SHOWN IN THE DRAWINGS AND NOT MENTIONED IN THE SPECIFICATIONS, OR REQUIRED BY THE SPECIFICATIONS AND NOT SHOWN ON THE DRAWINGS, SHALL BE PROVIDED AS IF FULLY PROVIDED FOR IN BOTH. IN THE CASE OF CONFLICTS BETWEEN THE DRAWINGS AND SPECIFICATIONS, OR WITHIN EITHER DOCUMENT, THE ENGINEER SHALL DETERMINE THE INTENT. IN SUCH CASES, IN GENERAL, THE MORE STRINGENT REQUIREMENT CONCERNING GREATER QUANTITY, QUALITY AND/OR RESULTING IN A HIGHER COST SHALL GOVERN WITHOUT FURTHER COST TO THE OWNER.</p> <p>C. SHUT-DOWN OF SYSTEM</p> <ol style="list-style-type: none"> COORDINATE AND SEQUENCE DEMOLITION SO AS NOT TO CAUSE SHUTDOWN OF OPERATION OF SURROUNDING AREAS. SHUT-DOWN PERIODS: <ol style="list-style-type: none"> ARRANGE TIMING OF SHUT-DOWN PERIODS OF SYSTEM, SERVICE WITH OWNER. DO NOT SHUT DOWN ANY SERVICE, WITHOUT PRIOR WRITTEN APPROVAL. PROVIDE NOTICE MINIMUM 15 WORKING DAYS IN ADVANCE. KEEP SHUT-DOWN PERIOD TO MINIMUM OR USE INTERMITTENT PERIOD AS DIRECTED BY THE OWNER. MAINTAIN LIFE-SAFETY SYSTEM IN FULL OPERATION IN OCCUPIED FACILITIES, OR PROVIDE NOTICE MINIMUM 15 WORKING DAYS IN ADVANCE. THE SYSTEM SHUT-DOWN SHALL BE DONE DURING OFF-BUSINESS HOURS. VISIT TO SITE <ol style="list-style-type: none"> THIS CONTRACTOR SHALL CAREFULLY EXAMINE THE ENTIRE SET OF CONTRACT DOCUMENTS, VISIT THE SITE, AND FULLY FAMILIARIZE HIMSELF/HERSELF AS TO ALL CONDITIONS AND MATTERS THAT CAN AFFECT THE WORK OR THE COST THEREOF. THIS CONTRACTOR IS RESPONSIBLE FOR NOTIFYING ENGINEER IN WRITING, AND PRIOR TO BID, OF DISCREPANCIES OR OMISSIONS FROM THE DRAWINGS, SPECIFICATIONS OR OTHER DOCUMENTS. OBTAIN CLARIFICATION PRIOR TO SUBMITTING ANY BID. LOSS OF NOTIFICATION SHALL BE INTERPRETED TO INDICATE NO DISCREPANCIES OR CONFLICTS EXIST AND ADDITIONAL COMPENSATION WILL NOT BE GRANTED AFTER AWARD OF CONTRACT FOR ANY WORK REQUIRED TO COMPLY WITH THESE REQUIREMENTS OR INTENT. SUBMISSION OF PROPOSALS SHALL BE CONSIDERED EVIDENCE THAT THE CONTRACTOR HAS VISITED AND EXAMINED THE SITE. NO EXTRA PAYMENT WILL BE ALLOWED THE CONTRACTOR FOR EXTRA WORK CAUSED BY FAILURE TO VISIT, EXAMINE AND VERIFY. THE ENGINEER WILL MAKE PERIODIC VISITS TO THE JOBSITE TO OBSERVE THE PROGRESS OF THE WORK AND TO OBSERVE ITS ACCORDANCE WITH THE CONTRACT DOCUMENTS. THE ENGINEER IS NOT A GUARANTOR OF THE CONTRACTOR'S WORK, RESPONSIBLE FOR JOB SITE SAFETY, RESPONSIBLE FOR SUPERINTENDING, OR IN CHARGE OF THE ERECTION AND/OR CONSTRUCTION OF THE WORK. THE ENGINEER IS NOT RESPONSIBLE FOR SAFETY OR ADEQUACY OF ANY SHIPMENT, BUILDING, SCAFFOLDING, FORMS OR OTHER WORK AIDS USED. LAWS, ORDINANCES, AND REGULATIONS <ol style="list-style-type: none"> ALL SYSTEMS SHALL CONFORM IN FULL AND/OR PART SHALL CONFORM TO ALL PERTINENT LAWS, ORDINANCES AND REGULATIONS OF ALL BODIES HAVING JURISDICTION AT ALL GOVERNING LEVELS, NOTWITHSTANDING ANYTHING IN THESE DRAWINGS OR SPECIFICATIONS TO THE CONTRARY. IN CASE OF CONFLICT BETWEEN GOVERNING LEVELS, THE MORE STRINGENT LAWS SHALL APPLY. THE CONTRACTOR SHALL PAY ALL FEES AND OBTAIN AND PAY FOR ALL PERMITS AND INSPECTIONS REQUIRED BY ANY AUTHORITY HAVING JURISDICTION IN CONNECTION WITH HIS WORK. WHERE APPLICABLE, ALL NEW MATERIAL SHALL BEAR THE UNDERWRITERS (UL) SEAL OF APPROVAL, AS WELL AS THOSE SEALS OF ALL MUNICIPALITIES HAVING JURISDICTION. CERTIFICATES TO THIS AFFECT TO BE FURNISHED TO ARCHITECT UPON REQUEST. THE ELECTRICAL CONTRACTOR SHALL SECURE AND PAY FOR ALL LICENSES REQUIRED BY THE GOVERNING BODIES TO OPERATE AS AN ELECTRICAL CONTRACTOR FOR THIS PROJECT. ALL LIGHT FIXTURES, RECEPTACLES, AND ELECTRICAL COMPONENTS SHALL BE DISPOSED IN CONFORMANCE WITH EPA REGULATION. WORKMANSHIP <ol style="list-style-type: none"> ALL WORK TO BE PERFORMED SHALL BE DONE BY QUALIFIED MECHANICS. ALL MECHANICS IN THE EMPLOY OF THIS CONTRACTOR ON THIS PROJECT SHALL BE SKILLED IN THE PHASES OF THE WORK TO WHICH THEY ARE USED. ALL WORK MUST BE DONE IN WORKMANLIKE MANNER TO THE COMPLETE SATISFACTION OF THE ENGINEER. ALL MATERIAL SHALL BE NEW, OF THE QUALITY SPECIFIED, FREE FROM DEFECTS AND IN FIRST-CLASS CONDITION. ALL VERTICAL CONDUITS SHALL BE PLUMB. THE COMPLETE SYSTEM SHALL MEET THE REQUIREMENTS OF THE LOCAL ELECTRICAL CODE AND AS MAY BE MODIFIED BY LOCAL ORDINANCES. THIS CONTRACTOR SHALL ESTABLISH SAFE WORKING PROCEDURES FOR THE PROTECTION OF THE WORK CREW AND NON-WORKING OCCUPANTS IN ALL PHASES OF WORK, COMPLYING WITH THE APPLICABLE PROVISIONS OF ALL CITY, STATE AND FEDERAL SAFETY LAWS (OSHA). THIS SHALL INCLUDE "LOCK-OUT/TAG-OUT" AND REQUIRED GROUNDING. WORK UNDER THIS CONTRACT SHALL NOT BE DONE ON ENERGIZED CIRCUITS. COORDINATION WITH OTHER TRADES <ol style="list-style-type: none"> THE SEQUENCE FOR THE INSTALLATION OF ALL WORK SHALL BE COORDINATED BETWEEN ALL CONTRACTORS ON THE PROJECT AND IN STRICT ACCORDANCE WITH ENGINEER AND OWNERS STIPULATION AS CALLED FOR IN THE SPECIFICATION AND/OR AS DIRECTED. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING THE LABOR AND SOFT MATERIALS REQUIRED FOR COORDINATING CONSTRUCTION INSTALLATION ELECTRONICALLY WITH OTHER TRADES USING CURRENT SOFTWARE AND MODELING SYSTEMS. THE CONTRACTOR SHALL CONFIRM MODELING REQUIREMENTS PRIOR TO BID. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING HIS WORK WITH THAT OF THE OTHER TRADES. CONTRACTOR IS COMPLETELY RESPONSIBLE IF FAILURE ON HIS PART TO COORDINATE EFFORTS RESULTS IN EXTRA WORK HAVING TO BE DONE TO COMPLETE A TASK AS SUCH, HIS FAILURE SHALL NOT BE THE BASIS FOR ANY EXTRA CHARGE AGAINST THE OWNER. CONTRACTOR SHALL CHECK DRAWINGS OF OTHER TRADES TO VERIFY THAT SPACES IN WHICH THEIR WORK WILL BE INSTALLED IS CLEAR OF OBSTRUCTIONS. WORK SHALL BE INSTALLED TO MAINTAIN MAXIMUM HEADROOM AND SPACE CONDITION AT ALL POINTS IN THE BUILDING WHERE HEADROOM OR SPACE CONDITIONS APPEAR INADEQUATE. CONTRACTOR SHALL NOTIFY ENGINEER BEFORE PROCEEDING WITH THE INSTALLATION OF THEIR WORK. CONTRACTOR SHALL FURNISH OTHER TRADES ADVANCE INFORMATION AND/OR SHOP DRAWINGS ON LOCATIONS AND SIZES OF CONDUITS, RACEWAYS, EQUIPMENT, FRAMES, BOXES, SLEEVES AND OPENINGS, ETC. NEEDED FOR THEIR WORK TO PERMIT OTHER TRADES AFFECTED TO INSTALL THEIR WORK PROPERLY AND WITHOUT DELAY. WHERE THERE IS EVIDENCE THAT WORK OF ONE TRADE WILL INTERFERE WITH WORK OF OTHER TRADES, ALL TRADES SHALL MEET ON JOB SITE TO WORK OUT SPACE CONDITIONS, AND MAKE SATISFACTORY ADJUSTMENTS TO INSTALLATION OF THE NEW WORK. CONTRACTOR SHALL VERIFY EXACT LOCATIONS OF ALL ELECTRICAL DEVICES AND EQUIPMENT PRIOR TO ROUGH-IN WITH FIELD CONDITIONS, SHOP DRAWINGS AND WORK OF OTHER TRADES. EACH CONTRACTOR SHALL BE RESPONSIBLE, AT THEIR OWN EXPENSE, FOR THE REMOVAL AND REINSTALLATION OF ANY PART OF THEIR WORK IF SAME WAS INSTALLED WITHOUT CONSULTING WITH OTHER TRADES BEFORE INSTALLING THEIR WORK. REFER TO THE ARCHITECTURAL, MECHANICAL AND PLUMBING SHEETS AND SPECIFICATIONS FOR EQUIPMENT LOCATIONS, LOADS, AND ADDITIONAL REQUIREMENTS. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH MECHANICAL CONTRACTOR FOR EXACT LOCATION OF HVAC EQUIPMENT TO BE WIRED PRIOR TO ROUGH-IN. THE EC SHALL REVIEW AND BE FAMILIAR WITH THE MECHANICAL DRAWINGS AND SCHEDULES FOR FINAL EQUIPMENT SELECTION. THE EC SHALL VERIFY HORSEPOWER, VOLTAGE, PHASES, AMPACITY, AND SPECIAL MOUNTING BEFORE SUBMITTING HIS BID. ANY SPECIAL CONDITIONS OR CONFLICTS MUST BE INDICATED IN WRITING TO THE ENGINEER PRIOR TO OR AT THE TIME OF BID. BEFORE STARTING ANY DEMOLITION ON HVAC EQUIPMENT WHICH HAS AN ELECTRICAL CONNECTION, THE MECHANICAL CONTRACTOR SHALL MEET WITH THE ELECTRICAL CONTRACTOR TO IDENTIFY ALL SUCH EQUIPMENT. THE ELECTRICAL CONTRACTOR WILL DISCONNECT THE POWER TO EACH UNIT, REMOVE CONDUIT, WIRING, DISCONNECT SWITCHES, AND STARTERS UNDER HIS CONTRACT. MECHANICAL CONTRACTOR WILL REMOVE ALL EQUIPMENT, ELECTRICAL TEMPERATURE CONTROL AND WIRING UNDER HIS CONTRACT. MECHANICAL CONTRACTOR SHALL NOT START DEMOLITION UNTIL ALL ELECTRICAL POWER HAS BEEN SAFELY DISCONNECTED FROM EQUIPMENT TO BE DEMOLISHED. 013000. SUBMITTALS <ol style="list-style-type: none"> THE CONTRACTOR SHALL PROVIDE COMPLETE SHOP DRAWINGS INDICATING EQUIPMENT, DEVICE, AND RACEWAY LOCATIONS, INVERTS FOR OUTDOOR DEVICES, AND COMPLETE INSTALLATION DRAWINGS. DRAWINGS SHALL BE IN AUTOCAD FORMAT AND SUBMITTED TO THE ENGINEER. THE CONTRACTOR SHALL USE ONLY TRAINED AND AUTHORIZED PROFESSIONAL ELECTRICAL CRAFT PERSONS. THE E.C. SHALL FURNISH ANY PERSONNEL SAFETY EQUIPMENT, LADDERS, MAN-LIFTS, AND POWERED HAND TOOLS THAT MAY BE REQUIRED. ALL POWERED TOOLS SHALL BE IN GOOD CONDITION WITH ALL GROUND CONDUCTOR IN PROPER OPERATION. VERIFY CODE CLEARANCES FOR ALL NEW ELECTRICAL WORK BEFORE PROCEEDING WITH CONSTRUCTION. PROVIDE ADEQUATE WORKING CLEARANCES, DEDICATED EQUIPMENT SPACE, AND LEAK PROTECTION SYSTEMS AS REQUIRED BY APPLICABLE ELECTRICAL CODES. COORDINATE USAGE OF AVAILABLE SPACE WITH ALL TRADES. IN THE EVENT OF CONFLICTS, NOTIFY THE ENGINEER BEFORE PROCEEDING WITH THE WORK. CONFlict IN DOCUMENTS <ol style="list-style-type: none"> PROVIDE PRODUCT DATA FOR ALL EQUIPMENT AND DEVICES SUCH AS PANELBOARDS, DISCONNECT SWITCHES, CONDUIT & JUNCTION BOXES, WIRES, GROUNDING MATERIALS, WIRING DEVICES, EMERGENCY GENERATOR, PIPING MATERIALS, VALVES, ETC. PROVIDE DIMENSIONAL DRAWINGS, MANUFACTURERS' TECHNICAL DATA, PERFORMANCE, ELECTRICAL CHARACTERISTICS, RATINGS, AND FINISHES. INCLUDE WIRING DIAGRAMS FOR POWER, SIGNAL, AND CONTROL WIRING. 	<p>D. PROVIDE OPERATION AND MAINTENANCE DATA FOR ALL EQUIPMENT AND DEVICES INCLUDING MANUFACTURER'S WRITTEN INSTRUCTIONS FOR TESTING AND ADJUSTING EQUIPMENT AND DEVICES.</p> <p>E. PROVIDE SHOP DRAWINGS FOR CONDUITS LARGER THAN 1" AND ALL EXPOSED RACEWAYS.</p> <p>F. CONTRACTOR SHALL SUBMIT THE FOLLOWING ELECTRONIC FILES TO THE ENGINEER AND OWNER AS PART OF THE CLOSEOUT PACKAGE: <ol style="list-style-type: none"> REMOVE ALL UNUSED AND ABANDONED CONDUIT AND RACEWAY COMPLETELY. ALL SURFACE RACEWAY USED ON A FINISHED SURFACE MUST BE METALIC RACEWAY, WIREMOLD OR EQUAL. IF RACEWAY USED FOR POWER AND DATA, THEN MUST BE DUAL CHANNEL WITH PARTITION. ALL APPROVED SUBMITTALS, INCLUDING FINAL EQUIPMENT DATA SHEETS, CONTROL SEQUENCES, AND APPROVED SHOP DRAWINGS REFLECTING THE INSTALLED SYSTEMS. OPERATION AND MAINTENANCE MANUALS (IOMs), INCLUDING INSTALLATION INSTRUCTIONS, ROUTINE AND PREVENTIVE MAINTENANCE PROCEDURES, TROUBLESHOOTING GUIDES, AND PARTS LISTS FOR ALL MAJOR EQUIPMENT. AS-BUILT DRAWINGS, INCLUDING RECORD LOCATIONS OF CONTROL COMPONENTS, INCLUDING CONTROL UNITS, THERMOSTATS, AND SENSORS. REVISE SHOP DRAWINGS TO REFLECT ACTUAL INSTALLATION AND OPERATING SEQUENCES. FINAL ENGINEERING DRAWINGS FOR ALL DISCIPLINES. COMMISSIONING AND FUNCTIONAL TESTING REPORTS (AS APPLICABLE) DOCUMENT SYSTEM START UP, TESTING, ADJUSTING, AND BALANCING RESULTS. PUNCH LIST DOCUMENTATION AND COMPLETED SIGN OFFS, INCLUDING SIGNED CONFIRMATION THAT ALL PUNCH LIST ITEMS HAVE BEEN ADDRESSED AND RESOLVED. WARRANTY DOCUMENTATION, INCLUDING MANUFACTURER, PRIME CONTRACTOR, AND SUB-CONTRACTOR WARRANTIES, CLEARLY IDENTIFYING COVERAGE PERIODS, TERMS, AND START DATES. TRAINING DOCUMENTATION, INCLUDING TRAINING AGENDAS, PRESENTATION MATERIALS, AND SIGN-IN SHEETS VERIFYING OWNER PERSONNEL PARTICIPATION. PERMIT CLOSEOUT AND INSPECTION CERTIFICATES. COST SUMMARY AND FINAL PAY APPLICATIONS. VENDOR AND SUBCONTRACTOR CONTACT INFORMATION, INCLUDING NAMES, PHONE NUMBERS, EMAIL ADDRESSES, AND EMERGENCY CONTACTS. </p>	<p>H. ALL BOXES SHALL BE PROVIDED IN LOCATIONS WHERE REASONABLE ACCESS CAN BE OBTAINED IN THE FUTURE WITHOUT REQUIRING REMOVAL OF BUILDING ELEMENTS OR FINISHES. IT SHALL BE THE SOLE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR TO RELOCATE BOXES TO ACCESSIBLE AREAS WHERE INACCESSIBILITY IS DETERMINED BY THE INSPECTOR OR ENGINEER.</p> <p>I. END OF CONDUIT AND RACEWAY SHALL BE INSULATED AND TIGHTLY TIED. ALL CONDUIT AND RACEWAY SHALL BE TIGHTLY TIED TO THE CONCRETE OR METAL CONSTRUCTION.</p> <p>J. ANY SURFACE RACEWAY USED ON A FINISHED SURFACE MUST BE METALIC RACEWAY, WIREMOLD OR EQUAL. IF RACEWAY USED FOR POWER AND DATA, THEN MUST BE DUAL CHANNEL WITH PARTITION.</p> <p>K. FINAL CONNECTIONS TO MOBILE DEVICES, OR DEVICES THAT MAY TRANSMIT VIBRATION SHALL BE MADE THROUGH FLEXIBLE METALIC CONDUIT OR LIQUID-TIGHT FLEXIBLE CONDUIT. (MOTORS, TRANSFORMERS, DUCT MOUNTED DEVICES, ETC.)</p> <p>L. ENDS OF ALL METALLIC CONDUIT SHALL BE EQUIPPED WITH INSULATED GROUNDING BUSHINGS FOR DEDICATED CONDUITS SERVING GROUNDING CONDUCTORS. ALL METALLIC CONDUIT SERVING FEEDERS AND OTHER CIRCUITS SHALL BE EQUIPPED WITH INSULATED ANTI-SPLIT FITTINGS AT ENDS. ENDS OF ALL CONDUIT SHALL BE TEMPORARILY CAPPED PRIOR TO INSTALLATION AND DURING CONSTRUCTION TO EXCLUDE FOREIGN MATERIAL UPON THE COMPLETION OF CONSTRUCTION THE OPEN END OF CONDUITS OR SLEEVES SHALL BE SEALED WATERTIGHT.</p> <p>M. EACH LIGHT, RECEPTACLE OR OTHER MISCELLANEOUS DEVICE SHALL BE PROVIDED WITH A GALVANIZED OR SERRATED PRERESSED STEEL OUTLET BOX OF THE KNOCKOUT TYPE, OR NOT LESS THAN 1/2 INCHES IN DIAMETER. CONDUIT AND BOXES SHALL BE FASTENED WITH LOCK NUTS AND BUSHINGS. ALL INSULATED BOX NICKOUTS MUST BE LEFT SEALED. THERE MUST BE SUFFICIENT ROOM FOR WIRES AND BUSHINGS. AND, DEEP BOXES SHALL BE INSTALLED WHERE REQUIRED. BOXES SHALL BE SECURELY AND ADEQUATELY SUPPORTED.</p> <p>N. WHERE FLOOR FITTINGS REQUIRE PENETRATION OF THE FLOOR SLAB, THERE SHALL BE A STANDARD DEVICE LISTED BY UL FOR THE PURPOSE AND HAVE A UL FILE NUMBER EQUAL TO THE FLOOR RATING. ALL CONDUIT AND BOXES LOCATED IN THE FLOOR SHALL BE SUPPORTED BY THE CONTRACTOR. SUBMISSION TO STRUCTURAL ENGINEER PRIOR TO CORING, THE ELECTRICAL CONTRACTOR MUST PROVIDE FLOOR X-RAY SERVICES TO DETECT AND AVOID EXISTING EMBEDDED SYSTEMS PRIOR TO CORING.</p> <p>O. ALL CONDUIT RUNS SHALL BE INSTALLED ABOVE AND OVER TOP OF ALL NEW DUCTWORK, PIPING, CONDUITS, PULL BOXES, ETC. WITH PROVISION FOR ALL NECESSARY ACCESSIBLE PULL BOXES. CONDUIT MAY NOT EXCEED CODE ALLOWED NUMBER OF BENDS.</p> <p>P. CONDUIT RUNS OR PULL BOXES SHALL NOT BLOCK OR PREVENT FULL ACCESS OR OPERATION OF HVAC EQUIPMENT, ACCESS DOORS, PIPING VALVES, JUNCTION BOXES, MAIN RETURN AIR DUCTS, PULL BOXES, CLEAN OUTS, ETC.</p> <p>Q. FLEXIBLE METAL CONDUIT SHALL NOT BE LONGER THAN 6' 0" LONG.</p>	<p>262816.19 ENCLOSED SWITCHES</p> <p>b. HUBBELL</p> <p>c. LEGRAND</p> <p>b. TOGGLE SWITCHES SHALL BE SINGLE UNIT TOGGLE, BUTT CONTACT, QUIET AC TYPE, HEAVY DUTY GENERAL-PURPOSE USE WITH AN INTEGRAL SELF GROUNDING MOUNTING STRAP, LISTED BY UNDERWRITERS LABORATORIES, INC., AND MEET THE REQUIREMENTS OF NEMA WD 1, HEAVY DUTY AND UL 20 RATED FOR 20 AMPERES AT 120-277 VOLTS AC.</p> <p>c. WALL PLATES FOR RECEPTACLES SHALL BE TYPE 302 BRUSHED STAINLESS STEEL IN PUBLIC AREAS AND GALVANIZED STEEL IN MAINTENANCE AREAS. ALL DEVICES MOUNTED EXPOSED TO WEATHER SHALL BE MOUNTED IN CAST ALUMINUM ENCLOSURES THAT ARE NEMA RATED 3R OR 4. WIRE DEVICES MANUFACTURERS LEVITON, HUBBELL OR APPROVED EQUAL.</p>
<p>B. CONFLICT IN DOCUMENTS</p> <p>017800. CLOSEOUT SUBMITTALS</p> <p>A. CLOSEOUT DOCUMENT AND EQUIPMENT TURNOVER <ol style="list-style-type: none"> FINAL AS-BUILT DRAWINGS IN ELECTRONIC PDF FORMAT TO OWNER AND ENGINEER SHOWING FINAL INSTALLED CONDITIONS AND BEFORE FINAL PAYMENT WILL BE ISSUED. AS-BUILT DRAWINGS SHALL DIAGRAMMATICALLY INDICATE THE INSTALLED CONDITION, CIRCUIT NUMBERS, AND LOCATION OF THE DEVICES FOR ALL WORK. THESE DRAWINGS SHALL BE CONSIDERED CONTRACT RECORD DOCUMENTS AND SHALL ACCURATELY REFLECT THE ACTUAL INSTALLATION OF THE ELECTRICAL COMPONENTS AND CONDUITS. PROVIDE ALL EQUIPMENT INSTALLATION, MAINTENANCE, AND INSTRUCTION MANUALS. TURN OVER ALL KEYS, SPARE MATERIALS, STOCK ITEMS, AND OTHER EQUIPMENT PURCHASED AS PART OF THE CONTRACT AND BELONGING TO THE OWNER. </p> <p>017900. DEMONSTRATION AND TRAINING</p> <p>B. TESTING <ol style="list-style-type: none"> PERFORM TESTS RECOMMENDED BY MANUFACTURER INCLUDING VISUAL, MECHANICAL, AND ELECTRICAL INSPECTIONS. PERFORM INSULATION-RESISTANCE TESTS IN ACCORDANCE WITH IEEE 43. FUNCTIONALLY TEST EQUIPMENT TO ENSURE IT IS INSTALLED PER DESIGN. PROVIDE OPERATIONAL TEST AFTER ELECTRICAL CIRCUITRY HAS BEEN ENERGIZED, CONFIRM PROPER OPERATION. PROVIDE WRITTEN REPORT OF THE RESULTS OF TESTS AND INSPECTIONS. PERFORM TESTS RECOMMENDED BY MANUFACTURER INCLUDING VISUAL AND MECHANICAL AND ELECTRICAL INSPECTIONS. FUNCTIONALLY TEST EQUIPMENT TO ENSURE IT IS INSTALLED PER DESIGN. PROVIDE OPERATIONAL TEST AFTER ELECTRICAL CIRCUITRY HAS BEEN ENERGIZED, CONFIRM PROPER OPERATION. PROVIDE WRITTEN REPORT OF THE RESULTS OF TESTS AND INSPECTIONS. PERFORM WRITTEN REPORT OF THE RESULTS OF TESTS AND INSPECTIONS. PERFORM OPERATIONAL TEST AFTER ELECTRICAL CIRCUITRY HAS BEEN ENERGIZED, CONFIRM PROPER OPERATION. PROVIDE WRITTEN REPORT OF THE RESULTS OF TESTS AND INSPECTIONS. </p> <p>017900. DEMONSTRATION AND TRAINING</p> <p>C. GUARANTEE <ol style="list-style-type: none"> THIS CONTRACTOR SHALL UNCONDITIONALLY GUARANTEE IN WRITING ALL MATERIAL, EQUIPMENT AND WORKMANSHIP FOR A PERIOD OF ONE YEAR FROM DATE OF ACCEPTANCE BY OWNER. THE CONTRACTOR SHALL PROVIDE FREE SERVICE FOR ALL EQUIPMENT INVOLVED IN HIS CONTRACT DURING THIS GUARANTEE PERIOD. THE GUARANTEE SHALL INCLUDE RESTORATION TO ITS ORIGINAL CONDITION OF ALL ADJACENT WORK THAT MUST BE DISTURBED IN FULFILLING THIS GUARANTEE. ALL SUCH REPAIRS AND/OR REPLACEMENTS SHALL BE MADE WITHOUT DELAY AND AT THE CONVENIENCE OF THE DEVELOPER AND TENANT. </p> <p>D. WARRANTY <ol style="list-style-type: none"> INSTALLER AND MANUFACTURERS AGREE TO REPAIR OR REPLACE MATERIALS OR WORKMANSHIP THAT FAIL WITHIN SPECIFIED WARRANTY PERIOD. WARRANTY PERIOD SHALL BE ONE YEAR FROM DATE OF SUBSTANTIAL COMPLETION. </p> <p>E. INSPECTION <ol style="list-style-type: none"> ALL ELECTRICAL WORK IS TO BE INSPECTED AND APPRO</p>					